MEASUREMENT OF THE CALIFORNIA COUNTER-CURRENT

By Keith Coddington

NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

MEASUREMENT OF THE
CALIFORNIA COUNTERCURRENT

by

Keith Coddington

June 1979

Thesis Advisors: J. B. Wickham
S. P. Tucker

Approved for public release; distribution unlimited.

Thesis
C53025

T191027

Thesis
C53025
c.1

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Measurement of the California Countercurrent		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; June 1979 6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Keith Coddington		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		12. REPORT DATE June 1979 13. NUMBER OF PAGES 135
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

California Countercurrent
California Undercurrent
Davidson Current
California Current

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Direct measurements by moored current meters and indirect measurements from geostrophy are compared and discussed for a region over the continental slope off central California during the Davidson Current period.

During that same period vertical temperature and salinity profiles were made at 23 stations on four separate cruises in the study area south of Monterey, California. These arrays of

#20 - ABSTRACT - CONTINUED

moored current meters simultaneously recorded the flow of the current at specified levels.

The California Countercurrent was found to be present in the region of study during the entire observation period. Its offshore position and extent, its intensity and its vertical location and extent varied in a way largely consistent with its reported behavior in other locations along the U.S. West Coast.

Approved for public release; distribution unlimited.

Measurement of the California Countercurrent

by

Keith Coddington
Lieutenant, United States Coast Guard
B.S., United States Coast Guard Academy, 1973

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN OCEANOGRAPHY

from the

NAVAL POSTGRADUATE SCHOOL

June 1979

ABSTRACT

Direct measurements by moored current meters and indirect measurements from geostrophy are compared and discussed for a region over the continental slope off central California during the Davidson Current period.

During that same period vertical temperature and salinity profiles were made at 23 stations on four separate cruises in the study area south of Monterey, California. These arrays of moored current meters simultaneously recorded the flow of the current at specified levels.

The California Countercurrent was found to be present in the region of study during the entire observation period. Its offshore position and extent, its intensity and its vertical location and extent varied in a way largely consistent with its reported behavior in other locations along the U.S. West Coast.

TABLE OF CONTENTS

I. INTRODUCTION ---------- 13

A. THE CALIFORNIA CURRENT SYSTEM ---------- 13

B. PREVIOUS STUDIES OF THE CALIFORNIA UNDERCURRENT ---------- 14

C. STATEMENT OF THE PROBLEM ---------- 19

II. AREA OF INVESTIGATION ---------- 24

III. SALINITY-TEMPERATURE-DEPTH OBSERVATIONS ------- 27

A. INSTRUMENTATION AND DATA COLLECTION ------- 27

B. RESULTS ---------- 28

C. DISCUSSION OF WATERMASS PROPERTIES AND GEOSTROPHY ---------- 29

IV. DIRECT CURRENT OBSERVATIONS ---------- 54

A. INSTRUMENTATION AND DATA COLLECTION ------- 54

B. DISCUSSION OF DIRECT CURRENT MEASUREMENTS - 58

V. COMPARISON OF GEOSTROPHY WITH DIRECT CURRENT MEASUREMENTS ---------- 70

VI. CONCLUSIONS ---------- 73

APPENDIX A: NOYFB PROGRAM ---------- 76

APPENDIX B: TEMPERATURE, SIGMA-T, SOUND SPEED, AND SIGMA-T AND SALINITY SUPERIMPOSED VERTICAL SECTIONS ---------- 99

BIBLIOGRAPHY ---------- 131

INITIAL DISTRIBUTION LIST ---------- 134

LIST OF TABLES

TABLES		PAGE
I.	Latitude, longitude and depth of stations --	26
II.	Comparison of current meter and geostrophic current velocities on 27 November 1978 and 8 January 1979 ----------	75

LIST OF FIGURES

FIGURE		PAGE
1.	Temperature-salinity curves from selected stations (Sverdrup and Johnson, 1941) ----------	21
2.	Diagram showing T-S curves defining percentage southern water (Sverdrup and Johnson, 1941) ----	21
3.	Mean dynamic topography of the sea surface reference 500 db during January off California and Baja California (Hickey, 1978) ----------	22
4.	Mean dynamic topography of the 200 db surface reference 500 db during January off California and Baja California (Hickey, 1978) --	22
5.	Temperature-salinity relationships for selected stations in California undercurrent (Wooster and Jones, 1970) ----------	23
6.	Chart indicating area of investigation and stations ----------	25
7.	Salinity (‰) on a vertical section for the Cape San Martin line on 27-28 November 1978 ----	34
8.	Salinity (‰) on a vertical section for the Slate Rock line on 27-28 November 1978 ---------	35
9.	Salinity (‰) on a vertical section for the Cape San Martin line on 8-9 January 1979 -------	36
10.	Salinity (‰) on a vertical section for the Slate Rock line on 8-9 January 1979 ----------	37
11.	Salinity (‰) on a vertical section for the Cape San Martin line on 22-23 January 1979 -----	38
12.	Salinity (‰) on a vertical section for the Slate Rock line on 22-23 January 1979 ----------	39
13.	Salinity (‰) on a vertical section for the Cape San Martin line on 21-22 February 1979 ----	40
14.	Salinity (‰) on a vertical section for the Slate Rock line on 21-22 February 1979 ---------	41
15.	Dynamic topography of the 100/500 db surface on 27-28 November 1978 ----------	42

FIGURE PAGE

16. Dynamic topography of the 200/500 db surface on 27-28 November 1978 ---------- 42

17. Dynamic topography of the 300/500 db surface on 27-28 November 1978 ---------- 42

18. Dynamic topography of the 100/500 db surface on 8-9 January 1979 ---------- 43

19. Dynamic topography of the 200/500 db surface on 8-9 January 1979 ---------- 43

20. Dynamic topography of the 300/500 db surface on 8-9 January 1979 ---------- 43

21. Dynamic topography of the 100/500 db surface on 22-23 January 1979 ---------- 44

22. Dynamic topography of the 200/500 db surface on 22-23 January 1979 ---------- 44

23. Dynamic topography of the 300/500 db surface on 22-23 January 1979 ---------- 44

24. Dynamic topography of the 100/500 db surface on 21-22 February 1979 ---------- 45

25. Dynamic topography of the 200/500 db surface on 21-22 February 1979 ---------- 45

26. Dynamic topography of the 300/500 db surface on 21-22 February 1979 ---------- 45

27. Vertical section of the normal component of geostrophic velocity for the Cape San Martin line on 27-28 November 1978 ---------- 46

28. Vertical section of the normal component of geostrophic velocity for the Slate Rock line on 27-28 November 1978 ---------- 47

29. Vertical section of the normal component of geostrophic velocity for the Cape San Martin line on 8-9 January 1979 ---------- 48

30. Vertical section of the normal component of geostrophic velocity for the Slate Rock line on 8-9 January 1979 ---------- 49

FIGURE PAGE

31. Vertical section of the normal component of geostrophic velocity for the Cape San Martin line on 22-23 January 1979 ---------- 50

32. Vertical section of the normal component of geostrophic velocity for the Slate Rock line on 22-23 January 1979 ---------- 51

33. Vertical section of the normal component of geostrophic velocity for the Cape San Martin line on 21-22 February 1979 ---------- 52

34. Vertical section of the normal component of geostrophic velocity for the Slate Rock line on 21-22 February 1979 ---------- 54

35. Array configuration ---------- 57

36. Progressive vector diagram for the current meter at station 2 at 220 meters depth from 25 July 1978 to 28 August 1978 ---------- 63

37. Progressive vector diagram for the current meter at station 2 at 190 meters depth from 20 September 1978 to 27 November 1978 ---------- 64

38. Progressive vector diagram for the current meter at station 2 at 100 meters depth from 27 November 1978 to 22 January 1979 ---------- 65

39. Progressive vector diagram for the current meter at station 2 at 175 meters depth from 27 November 1978 to 22 January 1979 ---------- 66

40. Progressive vector diagram for the current meter at station 2 at 300 meters depth from 27 November 1978 to 22 January 1979 ---------- 67

41. Progressive vector diagram for the current meter at station 5 at 140 meters depth from 27 November 1978 to 22 January 1979 ---------- 68

42. Progressive vector diagram for the current meter at station 5 at 215 meters depth from 27 November 1978 to 22 January 1979 ---------- 69

43. Temperature (°C) on a vertical section for the Cape San Martin line on 27-28 November 1978 - 99

44. Temperature (°C) on a vertical section for the Slate Rock line on 27-28 November 1978 ---------- 100

FIGURE PAGE

45. Temperature (°C) on a vertical section for the Cape San Martin line on 8-9 January 1979 -------- 101

46. Temperature (°C) on a vertical section for the Slate Rock line on 8-9 January 1979 ---------- 102

47. Temperature (°C) on a vertical section for the Cape San Martin line on 22-23 January 1979 ------ 103

48. Temperature (°C) on a vertical section for the Slate Rock line on 22-23 January 1979 ---------- 104

49. Temperature (°C) on a vertical section for the Cape San Martin line on 21-22 February 1979 ----- 105

50. Temperature (°C) on a vertical section for the Slate Rock line on 21-22 February 1979 ---------- 106

51. Sigma-t on a vertical section for the Cape San Martin line on 27-28 November 1978 ---------- 107

52. Sigma-t on a vertical section for the Slate Rock line on 27-28 November 1978 ---------- 108

53. Sigma-t on a vertical section for the Cape San Martin line on 8-9 January 1979 ---------- 109

54. Sigma-t on a vertical section for the Slate Rock line on 8-9 January 1979 ---------- 110

55. Sigma-t on a vertical section for the Cape San Martin line on 22-23 January 1979 ---------- 111

56. Sigma-t on a vertical section for the Slate Rock line on 22-23 January 1979 ---------- 112

57. Sigma-t on a vertical section for the Cape San Martin line on 21-22 February 1979 ---------- 113

58. Sigma-t on a vertical section for the Slate Rock line on 21-22 February 1979 ---------- 114

59. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 27-28 November 1978 - 115

60. Sound speed (m/sec) on a vertical section for the Slate Rock line on 27-28 November 1978 ------ 116

61. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 8-9 January 1979 ---- 117

FIGURE PAGE

62. Sound speed (m/sec) on a vertical section for the Slate Rock line on 8-9 January 1979 --------- 118

63. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 22-23 January 1979 -- 119

64. Sound speed (m/sec) on a vertical section for the Slate Rock line on 22-23 January 1979 ------- 120

65. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 21-22 February 1979 - 121

66. Sound speed (m/sec) on a vertical section for the Slate Rock line on 21-22 February 1979 ------ 122

67. Sigma-t and salinity (‰) superimposed on a vertical section for the Cape San Martin line on 27-28 November 1978 ------------------------- 123

68. Sigma-t and salinity (‰) superimposed on a vertical section for the Slate Rock line on 27-28 November 1978 ------------------------- 124

69. Sigma-t and salinity (‰) superimposed on a vertical section for the Cape San Martin line on 8-9 January 1979 ------------------------------ 125

70. Sigma-t and salinity (‰) superimposed on a vertical section for the Slate Rock line on 8-9 January 1979 ------------------------------- 126

71. Sigma-t and salinity (‰) superimposed on a vertical section for the Cape San Martin line on 22-23 January 1979 ------------------------- 127

72. Sigma-t and salinity (‰) superimposed on a vertical section for the Slate Rock line on 22-23 January 1979 ------------------------------ 128

73. Sigma-t and salinity (‰) superimposed on a vertical section for the Cape San Martin line on 21-22 February 1979 ------------------------- 129

74. Sigma-t and salinity (‰) superimposed on a vertical section for the Slate Rock line on 21-22 February 1979 ------------------------- 130

ACKNOWLEDGMENT

The author would like to express his sincere appreciation to his thesis advisors, Professor S.P. Tucker and Professor J.B. Wickham. Their knowledge and expertise in this project was only surpassed by their willingness to freely devote their time.

Special appreciation is extended to the Captain, W.W. Reynolds, and crew of the R/V ACANIA. Their highly skilled seamanship provided for smooth array installation and retrieval. Appreciation is also extended to Mr. Tim Stanton for his assistance in translating the current meter tapes.

Finally, a devoted thanks to my wife, Michelle, for her patience and understanding during this time.

I. INTRODUCTION

A. THE CALIFORNIA CURRENT SYSTEM

In the past decade eastern boundary currents and coastal upwelling have come under considerable scrutiny. This is due in part to their influence on the fishing industry and various other economic enterprises. Examples of eastern boundary current systems are the California, the Peru, the Benguela and the Canary Current Systems.

One eastern boundary current system, the California Current system is made up of an equatorward surface flow which extends along the entire west coast of the United States and Baja California and a counterflow, poleward, sometimes beneath this, at others on the surface shoreward of it. The equatorward surface flow is fed by the North Pacific Current, i.e. the northern limb of the North Pacific Gyre, and is known as the California Current. The poleward flow may be submerged, when it is then termed the California Undercurrent, or, at certain times of the year it may appear at the surface, when it is called the Davidson Current.

Reid, Roden and Wyllie (1958) apply the term California Current to all southward flow in the North Pacific Gyre. It is common to define the boundary of the California Current at a distance 1000 kilometers from shore (Hickey, 1978). High velocities are generally not encountered in this cold water mass.

The California Undercurrent is a poleward flow of water, the temperature and salinity of which is slightly higher than that of the surrounding water and which is usually found shoreward of the southward flowing California Current. It is much narrower and has a maximum of northward flow at intermediate depth. It is uncertain whether the Davidson Current is superimposed on the California Undercurrent, suppressing the core to great depths, or whether the Davidson Current is actually the expression of the undercurrent at the surface (Hickey, 1978).

The California Undercurrent is present year round and, with the onset of north-northwest winds and upwelling along California, it is found predominately below 200 meters. It is characterized by relatively high temperature, salinity and phosphate and low dissolved oxygen concentrations because of its southern origin. The undercurrent has been intensely studied off Oregon, Washington, and Southern California, but direct current measurements are lacking for the Central California region.

B. PREVIOUS STUDIES OF THE CALIFORNIA UNDERCURRENT

The California Undercurrent was first discussed by Sverdrup and Fleming (1941). During their cruises in 1937, they defined "northern water" on a T-S curve which showed an increase in salinity with decreasing temperature (Figure 1, curve C131). The T-S curve for "southern water" showed salinity relatively constant as temperature decreased (Figure 1,

curves 5.3 and B III, 31). They constructed a chart, defining percentage of southern water for given T-S pairs (Figure 2). Using these parameters they traced southern water as far north as Cape Mendocino. They also found that the southern water was close to the coast and was concentrated in the northward flowing current. They also showed the existence of the northward flowing undercurrent by means of dynamic heights.

Reid, Roden, and Wyllie (1958) expanded on Sverdrup and Fleming (1941) and Sverdrup, et al. (1942). They concluded the evidence for the undercurrent was of two sorts: (1) The warm or more saline subsurface water of low oxygen content suggested southern origin; and (2) geostrophic flow at the 200 decibar surface with respect to both the 500 and 1000 decibar surfaces indicated a northward flowing current, 30-60 miles in width near the coast north of 30°N and somewhat wider to the south.

Direct measurements of the undercurrent was made by Reid (1962, 1963) and Reid and Schwartzlose (1962) using drogues. Their results indicated the existence of a northward flowing current at 200 meters depth off Monterey, California, and Baja California. During the winter they found that a northward flow existed at the surface.

As a part of a California Cooperative Oceanic Fisheries Investigation (CALCOFI) study Wyllie (1966) showed the existence of a northward flowing undercurrent on the basis of dynamic topography. Wyllie's charts of mean monthly dynamic

topography on the 200 decibar surface relative to 500 decibars provide the best description of the flow of the undercurrent in January south of Cape Mendocine (Figures 3 and 4).

From Point Conception northward stronger subsurface flow was observed in winter than in summer. The weakest flow occured from March to May. Pavlova (1966) found that during the spring, when the undercurrent appears to be absent at the usual depth of about 200 meters, it may be present at depths exceeding 500 meters. Pavlova also concluded that the undercurrent actually reaches the surface during late fall and winter, when it is known as the Davidson Current. Wyllie's data supported these conclusions.

Wooster and Jones (1970) found that a characteristic of the undercurrent was a relatively high salinity bulge centered at sigma-t equal 26.54 (150 cl/t) on the T-S diagram (Figure 5). They also gave some evidence for an interannual variation in the northward extent of a given isohaline. They pointed out that a coastal deepening of isotherms and isopycnals and rising of isohalines are characteristics of the poleward undercurrent.

In the last ten years the study of the undercurrent has been concentrated north of Cape Mendocino and to some extent in the vicinity of Monterey, California. Mooers, Collins and Smith (1976) in their study of upwelling off the Oregon coast found a northward flow along the continental slope between 300 and 1000 meters. They suggested that it may exist

at greater depths and may extend from the continental slope to perhaps 500 kilometers from shore. Their primary observations were conducted during the same year and season as those of Wooster and Jones (1970). Mooers, et al, (1976) found that during July 1975, the near surface flow was predominately southward, and the near bottom flow alternated between northward and southward. In August and September 1965 and 1966 the near bottom flow was predominately northward.

Huyer and Smith (1976) and Halpern, Smith and Reed (1978) used direct measurements of current on the slope and shelf to describe the seasonal developments of the undercurrent off the coast of Oregon. Huyer and Smith's (1976) data suggest that the northward flow is present at depths greater than 400 meters in the spring but increases in speed and vertical extent as the season progresses. That the undercurrent was found at the shelf edge by summer is consistent with Pavlova's (1966) findings for northern California. Halpern, Smith, and Reed's (1978) current meter results support those of Huyer and Smith (1976). The data of both these studies suggest that the shelf and slope undercurrents were portions of the same flow.

Eddies are frequently observed off the coast of Vancouver Island, B.C. Mysak (1977) in conjunction with his study of the undercurrent suggests that the eddies are produced by baroclinic instability of the California Undercurrent. For the undercurrent he found a northward flow along the

continental slope but a southward flow farther offshore. Thus, off Vancouver Island the northward flowing California Undercurrent is essentially confined to the continental slope. The main core of the current at that latitude occurs around 300 meters.

Off Monterey, California, the undercurrent has been studied by Molnar (1972), Hughes (1975), Greer (1975), and Wickham (1975). Wickham (1975) used drogues and a continuous measuring salinity-temperature-depth profiler (STD). For August three main results were found in conjunction with the undercurrent: (1) At both 50 meters and 200 meters geostrophy and drogues both indicate that there is a narrow band of poleward flowing water near the shelf edge; (2) both drogues and geostrophy also indicate that there is a complex flow father west which seems to split the poleward flow into two branches; and (3) there is a broader poleward flow still farther west which is centered at 40-50 kilometers from the shelf edge.

An analytical model by McCreary (1977) indicated that, due to local wind forcing, the pycnocline tilts alongshore to balance the meridional component of the wind and results in an alongshore flow. This disturbance is not confined to the coast but propagates offshore and northward as a Kelvin-Rossby wave carrying along with it both the pycnocline deformation and the alongshore flow.

Hickey (1978) has examined most of the data to date. She found that the northward subsurface flow is generally

found off the west coast of North America over the continental slope. The flow on the 200 decibar surface is most continuous alongshore and strongest (south of Point Conception only) in summer and early fall. It is weakest and least continuous in the spring. North of Point Conception, the flow on the 200 decibar surface is stronger during winter than during summer and fall. She found that the depth of the high-speed core varied seasonally and that the flow appeared to have a jet-like structure, both vertically and horizontally and appeared to extend to the bottom over the slope. This is in agreement with McCreary (1977) who called this jet-like flow, quasi-geostrophic. In support of Wooster and Jones (1970), Hickey (1978) found that the salinity and temperature at the core of the undercurrent generally decreased from about 34.6‰ and 9.5°C off Baja California to about 33.9‰ and 7°C off Vancouver Island.

The flow from the surface to a depth of about 500 meters is confined to the continental slope, but the overall width of the region of northward flow has not been firmly established. The relationship between the undercurrent jet that occurs over the upper slope and the slower broader flow that occurs deeper in the water column farther offshore is uncertain.

C. STATEMENT OF THE PROBLEM

The presence of southern water can be inferred from isohalines, isotherms, and isopleths of sound speed; and the geostrophic current can be inferred from isopycnals. The

current can also be found through direct measurements by means of current meters. Wickham (1975) noted that a comparison of geostrophic observations with direct measurements of current would test the utility of geostrophy to describe flow in areas of complexity, such as off Monterey, California.

The initial objective of this study was to collect data by both means. This involved setting up stations where salinity, temperature and depth measurements could be taken and moored current meter arrays could be maintained. The thesis addresses the problems associated with the assembly and maintenance of the moored current arrays, the collection of salinity, temperature and depth data, and the analysis and interpretation of the direct and indirect current observations.



Figure 1. Temperature-salinity curves selected stations (Sverdrup and Johnson, 1941).



Figure 2. Diagram showing T-S curves defining percentage southern water (Sverdrup and Johnson, 1941.



Figure 3. Mean dynamic topography of the sea surface off California and Baja California relative to 500 db during January, contoured from data given by Wyllie (1966). Contour interval is 0.02 dynamic meters (Hickey, 1978).



Figure 4. Mean dynamic topography of the 200 db surface relative to 500 db off California and Baja California during January, contoured from data given by Wyllie (1966). Contour interval is 0.02 dynamic meters (Hickey, 1978).



Figure 5. Temperature-salinity relationships for selected stations in California undercurrent (Wooster and Jones, 1970).

II. AREA OF INVESTIGATION

The area of investigation is south of Monterey, California, as shown in Figure 6. Two lines of stations were established. The station locations and water depths are listed in Table I.

One of the reasons for positioning the stations on this part of the California coast is the relative simplicity of the bathymetric features. The depth contours run approximately parallel to the coast, and the shelf break is close to the coast. Another, but crucial, reason for using this part of the California coast is that it is less heavily fished than the areas immediately to the north and to the south. The current meter arrays are entirely subsurface with no surface markers. The presence of fishing activity increases the possibility of array damage or loss which we have tried to minimize through our selection of the study area.



Figure 6. Chart indicating area of investigation and stations. Depth contours in fathoms.

TABLE I

STATION	LATITUDE	LONGITUDE	DEPTH (METERS)
1	35-53.0	121-29.8	100
2	35-52.5	121-32.3	357
3	35-52.1	121-34.7	520
4	35-51.6	121-37.4	668
5	35-51.1	121-39.9	759
6	35-50.7	121-42.4	833
7	35-50.2	121-45.0	915
8	35-49.7	121-47.6	988
9	35-49.2	121-50.1	1061
10	35-48.7	121-52.7	1150
11	35-48.3	121-55.4	1182
12	35-47.8	121-57.7	1044
13	35-49.5	121-56.1	1274
14	35-51.1	121-54.6	1183
15	35-52.7	121-53.0	1146
16	35-54.3	121-51.3	1089
17	35-55.9	121-49.9	1080
18	35-57.6	121-48.3	1098
19	35-59.3	121-47.8	997
20	36-00.9	121-45.2	842
21	36-02.5	121-43.5	732
22	36-04.3	121-42.0	560
23	36-05.9	121-40.2	350

III. SALINITY-TEMPERATURE-DEPTH OBSERVATIONS

A. INSTRUMENTATION AND DATA COLLECTION

Watermass data was collected on four separate cruises of the R/V ACANIA, the oceanographic vessel of the Naval Postgraduate School. The cruises were on 27-28 November 1978, 8-9 January 1979, 22-23 January 1979, and 21-22 February 1979. During each cruise all 23 stations were occupied. Sampling of watermass properties was done where possible to 500 meters, the reference level used by CALCOFI (Wyllie, 1966).

For each cruise the primary instrument, a Bisset Berman Model 9006 STD , was used for delineating the vertical distributions of temperature and salinity. Nansen bottles and reversing thermometers provided independent measurements to check the calibration of the STD. Expendible bathythermograph (XBT) drops and surface temperature observations were made also at each station.

The analog recorder usually used with the Model 9006 STD was replaced on these cruises. The three separated signal frequencies were sent through a Hewlett-Packard Model 57307A VHF Switch with a 20 milisecond settling time to a Hewlett-Packard Model 5328A Universal Counter. The resulting binary coded decimal output was then read into the random access memory of a Hewlett-Packard 9831A desktop computer. After each complete profile the data was transferred to magnetic

tape. Profiles were recorded for both the descent and ascent of the STD.

Spikes in the salinity trace are known to be caused by a poorly matched time constant between the conductivity sensor and the platinum resistance thermometer used in the STD to correct the conductivity measurements to salinity. Salinity spikes were eliminated by comparison of descent and ascent profiles and XBT profiles. This was done by hand during examination of the profiles.

B. RESULTS

The results for each cruise are shown as vertical sections for both the Cape San Martin line and the Slate Rock line. Vertical sections are drawn for: salinity, temperature, sigma-t, sound speed, geostrophic currents, and sigma-t and salinity together. The dynamic topography of the 100 db, 200 db, and 300 db surfaces relative to 500 decibars is also given for the four separate cruises.

Salinity and temperature sections were contoured using data stored on the magnetic tapes from the HP 9831A computer after the salinity spikes had been removed. Sigma-t, geostrophic shear, and dynamic heights were calculated using the library computer program HYDRO, available at the Naval Postgraduate School for the IBM 360 computer. Sound speed was calculated using Wilson's equations (Wilson, 1960), available in the same program.

From the calculation of geostrophic shear mean values for four station intervals were found. This was done to

reduce the non-geostrophic contributions to the calculations which are inversely proportional to the distance over which geostrophic shear is averaged. Thus, resolution is diminished in order to give a more accurate picture of the larger scale circulation features.

Dynamic heights were smoothed in a similar manner. Values were averaged over three station heights. For station 12 the mean value was found using stations 11, 12, and 13. For the coastal stations 1 and 23 only two stations were used in the averaging, i.e., stations 1 and 2 and stations 22 and 23. For the coastal stations with less than 500 meters of water the stations were treated as if the depth were 500 meters and dynamic topographies were extrapolated from the first station seaward with such depth.

There are no results for stations 21, 22, and 23 during the cruise of 21-22 February 1979, as these stations were lost due to failure of the data recording equipment. On the same cruise there were four stations at five nautical mile intervals added to the west of station 12. This allowed computation of geostrophic shear out to station 12.

C. DISCUSSION OF WATERMASS PROPERTIES AND GEOSTROPHY

The presence of souther water is indicated by the distributions in two cross-sections of salinity, temperature, sigma-t, and sound speed on the series of four cruises. The current structure for the same series is deduced from geostrophic current sections and from dynamic topography at

three different levels, both currents and topographies being referred to 500 decibars. Direct current measurements are discussed later in Section IV.

Water with relatively high southern watermass properties is present below the pycnocline on the first cruise on 27-28 November 1978. This is particularly evident on the salinity sections, Figures 7 and 8. Both show a bulge of high salinity water below 200 meters, on Figure 7 for example between stations 3 and 10. The associated temperature and sound speed sections (Appendix B) also indicate the presence of southern water in this region. On this cruise the southern water characteristics appear below 200 meters and from about 4 kilometers to 38 kilometers offshore over the continental slope.

Geostrophy, Figures 27 and 28, indicates northward flow in the upper layers with a surface maximum of 25 to 30 cm/sec. The current appears to have two branches with weaker southward flow between them. Wickham (1975) found similar indications of branched flow farther offshore for his August data in the latitude of Monterey, and these were confirmed by drogue drifts. This branched northward flow is further shown at each of the three levels of contoured dynamic topography (100, 200, and 300 decibars, Figures 15, 16, and 17). Some southward flow appears at all three levels from stations 15 to 18. This is a small-scale feature and might not be real since small scales are not well resolved by geostrophy.

Comparison will be made in Section V between geostrophic and direct current measurements.

The cruise of 8-9 January 1979 also showed southern water; but, as Figures 9 and 10 show, the bulge of high salinity occurs farther west. The associated temperature and sound speed sections (Appendix B) also show this westward displacement of the southern water. Below 200 meters this southern water is found 15 kilometers farther offshore than on the last cruise. Although Pavlova (1966) and Hickey (1978) indicated the countercurrent moves offshore in the spring, our observations were made during the winter season. McCreary's (1977) view of the current's variations as manifestations of baroclinic Kelvin-like waves is consistent with this offshore movement.

Geostrophy in the cross-sections for 8-9 January 1979 (Figures 29 and 30) also shows the northward flow farther offshore. There is still a maximum at the surface, but with an increase in velocity to 70 cm/sec normal to the Cape San Martin line and 35 cm/sec normal to the Slate Rock line. There is an indication that this may be the shoreward branch of the northward flow found during the first cruise, as southward flow appears on the offshore edge of both sections. Dynamic topography (Figures 18, 19, and 20) shows this same pattern. At the 100 db level (Figure 18) the flow is intense and northward between stations 3 and 9. To the west of station 9 the flow intensity drops off sharply and southward flow appears between stations 13 and 15. To the east of

station 3 the dynamic topography is generally flat with northward flow indicated. At the 200 db level (Figure 19) the flow is weaker but is still northward between stations 3 and 9. Southward flow is now more evident between stations 13 and 15. At the 300 db level (Figure 20) the flow is southward with only a trace of northward flow between stations 15 and 17.

The cruise on 22-23 January 1979 shows reductions in southern water characteristics. All indicators, i.e., isopleths of salinity, temperature, sigma-t, and sound speed, are nearly parallel with only small horizontal gradients. Note that the 34.20 ‰ isohaline which in November lay in places higher in the water column than 200 meters is now at a depth of 300 meters, except within a few kilometers of the slope. This may indicate that southern water has moved seaward or deeper beyond the range of observations.

Geostrophy shows slight westward propagation of the northward flow (Figures 31 and 32, also, 21, 22, and 23). The flow appears slower, 20 cm/sec, and more diffuse. At the 200 db level (Figure 22) southward flow now exists shoreward of station 4. At the 300 db level (Figure 23) the flow has become more diffuse and the southern flow is now shoreward of stations 5 and 20.

The observations for the cruise of 21-22 February 1979 indicate an increase in salinity below 200 meters (Figures 13 and 14), the 34.20 ‰ isohaline having risen to a depth of 250 meters over most of both sections. The dynamic topography

(Figures 24, 25, and 26) now indicates a northward flow at stations 2 and 3 at the 200 db and 300 db levels. The geostrophic sections do not show this since the station averaging interval used in their construction does not permit calculations shoreward of station 4. This flow at the eastern stations and below 200 meters may be the start of the undercurrent.

An immediate observation must be made: The regions with indications of southern water and the regions where northward flow is indicated by geostrophy do not exactly coincide. For all the cruises considered, geostrophy shows a northward surface flow, in some instances with flow as great as 70 cm/sec, even though the watermass characteristics in some regions are not southern. This is not too surprising, since near the boundaries between watermasses, eddies and entrainment of anomalous water is common. The observed variations in salinity and velocity may also have alternative explanations. Passing eddies or meanders in the countercurrent might give results similar to those just discussed.

In the following section the currents inferred from geostrophy are compared to those measured directly by moored current meter arrays along the Cape San Martin line.



Figure 7. Salinity (‰) on a vertical section for the Cape San Martin line on 27-28 November 1978.



Figure 8. Salinity (‰) on a vertical section for the Slate Rock line on 27-28 November 1978.



Figure 9. Salinity (‰) on a vertical section for the Cape San Martin line on 8-9 January 1979.



Figure 10. Salinity (‰) on a vertical section for the Slate Rock line on 8-9 January 1979.



Figure 11. Salinity (‰) on a vertical section for the Cape San Martin line on 22-23 January 1979.



Figure 12. Salinity (‰) on a vertical section for the Slate Rock line on 22-23 January 1979.



Figure 13. Salinity (‰) on a vertical section for the Cape San Martin line on 21-22 February 1979.



Figure 14. Salinity (‰) on a vertical section for the Slate Rock line on 21-22 February 1979.



Figure 15. Dynamic topography of the 100/500 decibar surface on 27-28 November 1978. Units are in dynamic meters



Figure 16. Dynamic topography of the 200/500 decibar surface on 27-28 November 1978. Units are in dyanmic meters



Figure 17. Dynamic topography of the 300/500 decibar surface on 27-28 November 1978. Units are in dynamic meters



Figure 18. Dynamic topography of the 100/500 decibar surface on 8-9 January 1979. Units are in dynamic meters.



Figure 19. Dynamic topography of the 200/500 decibar surface on 8-9 January 1979. Units are in dynamic meters.



Figure 20. Dynamic topography of the 300/500 decibar surface on 8-9 January 1979. Units are in dynamic meters.



Figure 21. Dynamic topography of the 100/500 decibar surface on 22-23 January 1979. Units are in dynamic meters.



Figure 22. Dynamic topography of the 200/500 decibar surface on 22-23 January 1979. Units are in dynamic meters.



Figure 23. Dynamic topography of the 300/500 decibar surface on 22-23 January 1979. Units are in dynamic meters.



Figure 24. Dynamic topography of the 100/500 decibar surface on 21-22 February 1979. Units are in dynamic meters.



Figure 25. Dynamic topography of the 200/500 decibar surface on 21-22 February 1979. Units are in dynamic meters.



Figure 26. Dynamic topography of the 300/500 decibar surface on 21-22 February 1979. Units are in dynamic meters.



Figure 27. Vertical section of the normal component of geostrophic velocity in cm/sec for the Cape San Martin line on 27-28 November 1978. Southward flow indicated by cross hatched area.



Figure 28. Vertical section of the normal component of geostrophic velocity in cm/sec for the Slate Rock line on 27-28 November 1978. Southward flow indicated by cross hatched area.



Figure 29. Vertical section of the normal component of geostrophic velocity in cm/sec for the Cape San Martin line on 8-9 January 1979. Southward flow indicated by cross hatched area.



Figure 30. Vertical section of the normal component of geostrophic velocity in cm/sec for the Slate Rock line on 8-9 January 1979. Southward flow indicated by cross hatched area.



Figure 31. Vertical section of the normal component of geostrophic velocity in cm/sec for the Cape San Martin line on 22-23 January 1979. Southward flow indicated by cross hatched area.



Figure 32. Vertical section of the normal component of geostrophic velocity in cm/sec for the Slate Rock line on 22-23 January 1979. Southward flow indicated by cross hatched area.



Figure 33. Vertical section of the normal component of geostrophic velocity in cm/sec for the Cape San Martin line on 21-22 February 1979. Southward flow indicated by cross hatched area.



Figure 34. Vertical section of the normal component of geostrophic velocity in cm/sec for the Slate Rock line on 21-22 February 1979. Southward flow indicated by cross hatched area.

IV. DIRECT CURRENT OBSERVATIONS

A. INSTRUMENTATION AND DATA COLLECTION

Data collection was begun with the first array installed on 25 July 1978. This array contained one meter. The array was placed in 371 meters of water at approximately the position of station 2 (Figure 6) and remained in the water for one month. The second array was also placed near station 2 in 354 meters of water on 20 September 1978. The array contained one meter and remained in the water for two months. The meters from both the first and second array were placed at approximately 200 meters depth. Two larger arrays were installed on 27 November 1978. They contained three meters each and were installed in water of 353 meters depth near station 2 and 777 meters depth near station 5. The meters were situated at depths of 100, 175, and 300 meters. Both arrays remained in place until 22 January 1979.

Organization of each array was done by means of the NOYFB computer program. The original program was written by Donald Moller of the Woods Hole Oceanographic Institution in Fortran II for the Hewlett-Packard 2100 series. The program has been rewritten in Fortran IV for compatibility with the IBM 360 computer and is given in Appendix A. Through the use of on line terminals the program gives the operator a description of the mooring and its performance from an

operational point of view. Given environmental data and mooring components, the program presents the operator with mooring behavior information for evaluation of collected data as well as array design modifications. Step by step instructions for program operation are displayed to the user with the sequence determined by his selection of options. Standard mooring component characteristics (buoyancy, cross-sectional areas, elastic properties, etc.) are written into the program. These components are those used by Woods Hole Oceanographic Institution. Components which are non-standard with respect to the program are added during initialization or may be changed by an option.

The current meter used in these arrays is the Aanderaa Recording Current Meter Model 4 (RCM4). It is a self-contained instrument for recording speed, direction, and temperature of ocean currents with conductivity and pressure options. The RCM4 has a depth capability of 2000 meters. The RCM4 uses a rotor type current speed sensor, a magnetic compass, and a thermistor. An electro-mechanical encoder (analog to digital converter) samples and converts the measurements to binary digital signals which are then recorded on 1/4-inch magnetic tape. A sampling interval of 10 minutes was chosen for our meters. Input parameters for the RCM4 into the NOYFB program are: W(I) = -64.66 (buoyancy per meter length) and A(I) = +0.065 (area of component in square meters per meter length).

The array is arranged as in Figure 35 with no surface markers in order to keep all array elements out of the region of strong surface wave action. An acoustic release is used for retrieval of the arrays. It is an AMF Acoustic Release/Pinger Model 242, which is activated acoustically and also has a reply pinger used for interrogation and, if necessary, as a locating beacon.

Buoyancy for the array is provided by Benthos glass spheres. The glass spheres are 17-inches in diameter, housed in plastic hard hats and are capable to a depth of 6700 meters. They provide 55 pounds of buoyancy each and are connected together in pairs with 3/8-inch galvanized chain.

The wire finally used was 5/32-inch, 7x7 stainless steel wire, breaking strength about 2400 pounds, and stainless Nicopress fillings around plastic thimbles. Although the initial arrays used 1/4-inch galvanized wire with copper Nicopress fittings for terminations. Zinc anodes were attached to all Nicopress fittings, following a technique developed at Oregon State University (OSU). After one month of immersion the zincs on some of the wire fittings had almost totally disappeared. It was feared that a longer use would have led to corrosion of the copper Nicopress fittings and possibly to the loss of the array. It was then decided to use stainless steel wire. Again, following the technique developed at OSU, plastic 1/2-inch thimbles are used at all eye terminations. Galvanized anchor shackles with stainless steel cotterpins were used as connectors for



Figure 35. Array configuration.

the various components. Zincs are maintained on the meters and release as a protection against their corrosion. Input parameters for the wire into the NOYFB program are: W(I) = -0.1225 (weight of component in pounds per meter length), A(I) = +0.00397 (diameter in meters), RBS(I) = +2400.0 (rated breaking strength in pounds), and AW(I) = +0.065 (cross sectional metal area of wire in square inches).

Below each release is a 15-meter section of wire, 3-meter section of 3/8 inch chain and the weights. Weight is provided by scrap railroad wheels which have a weight of about 600 pounds per wheel in water. Two wheels are used for the shallow arrays and three for the deeper arrays.

Placement of arrays was done from the R/V ACANIA by the method of stringing the array out behind the ship, upper-most components first, and dropping the anchor last. As an added precaution a 7-foot cargo parachute was attached to the anchors to slow their rate of descent.

B. DISCUSSION OF DIRECT CURRENT MEASUREMENTS

All data obtained with the current meters was converted to speed and direction using Aanderaa calibration constants and consolidated on a single IBM compatible tape.

Current speed and direction were used to construct progressive vector diagrams. Vertical and horizontal scales are equal in these diagrams. The vertical axis is zero degrees, magnetic north. The coast in the study area is aligned approximately in a 305° magnetic direction.

The current at station 2 during the period 25 July to 28 August 1978 is depicted by the progressive vector diagram shown in Figure 36. This meter was at 220 meters depth. During its operation the average overall current was 336° magnetic at 7.6 cm/sec. With respect to the alignment of the coast this shows a slight onshore component.

The semidiurnal components in the currents are visible upon close examination (the crosses on the diagram appear at two-day intervals). Two reversals of current which last four-days each can be seen at the top of the figure.

The second meter was installed in September (Figure 37) at the same location, station 2, but at a depth of 190 meters. It was in operation from 20 September to 27 November 1978. For this period the progressive vector diagram is shown in Figure 37, and the crosses are located at three-day intervals. The mean flow was 318° magnetic at 2.9 cm/sec. During the middle of the observation period numerous reversals of flow appear. These oscillations suggest that the meter was near a frontal zone and that its position alternated between sides of that zone, perhaps as a meander or eddy in the counter-current moved through the station's position. The mean flow over the seventy days is dominated by the countercurrent flowing nearly parallel to the coast.

Figures 38 through 42 are progressive vector diagrams for the arrays in operation from 27 November 1978 to 22 January 1979 on moorings at stations 2 and 5. The crosses

in all these figures are at three-day intervals. Semi-diurnal components are again visible.

Figures 38, 39, and 40 are for the array at station 2. The upper meter was at 100 meters depth (Figure 38). The mean flow at this level was toward 337° magnetic at 12.8 cm/sec, a moderately strong onshore and northward flow. On the 8th of January the flow changes from northward to southward for three days. The next meter was at 175 meters depth (Figure 39). The mean flow was toward 321° magnetic at 3.2 cm/sec. This small mean value is deceiving; it results from a period of mainly southward flow during the first nine days and oscillations during the last part of the period. The speed during the middle of the period was at a maximum of 25 cm/sec during a three-day period. Thus, although the oscillations result in a small value for the local time-averaged flow, weakening of the countercurrent is not necessarily implied. The oscillations may simply imply a spatially fluctuating front in the region.

The bottom meter on this array was at 300 meters (Figure 40). The mean flow at this level was towards 151° magnetic at 1.8 cm/sec. During most of the period the flow appears weak and fluctuating. The oscillations are mainly in two directions, northward and southward parallel to the coast. The meter appears to be astride the front separating the countercurrent and the southward flow. As the countercurrent meanders the meter moves from one flow to the other. In summary the current is moderately strong and northward at

the surface and weak at mid-depth with the exception of the strong northward flow during the middle of the period. The oscillations during the first and last days and at the lower meter indicate a moving shear zone between the countercurrent and the southward flow.

Figures 41 and 42 are for the array installed at station 5 and operating in the interval 27 November 1978 through 22 January 1979. The upper meter was at 140 meters depth (Figure 41). The mean flow was toward 319° magnetic at 12.3 cm/sec. As can be seen, the flow is almost exclusively northward, parallel to the coast, during the entire period. The exception is a three-day interval at the start with southward flow.

At 215 meters (Figure 42) the mean flow was toward 308° magnetic at 6.3 cm/sec. This reduction of the mean from the upper meter is largely due to the southward flows during the first nine days and an eight-day period beginning about 1 January. During these reversals the flow maintains its new direction and intensity without multiple oscillations. The sharp, clear change in flow indicates reversal from countercurrent to southward flow with no lingering of the front in the region of the meter. This pattern is similar to that at station 2 with a weakening of flow with depth and the appearance of southward flow at the deeper meters.

In summary the mean flow at the surface during the period of 27 November 1978 through 22 January 1979 is northward with an onshore component and a surface maximum of speed. At mid-depth the current has maintained its direction

with reduced speed. At the deeper meters the flow is variable in direction and speed, indications of a frontal region separating northward and southward flow.



Figure 36. Progressive vector diagram for the current meter at 220 meters depth at station 2 from 25 July 1978 to 28 August 1978. Crosses are positioned at 2 day intervals. Vertical axis indicates Magnetic North.



Figure 37. Progressive vector diagram for the current meter at 190 meters depth at station 2 from 20 September 1978 to 27 November 1978. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.



Figure 38. Progressive vector diagram for the current meter at 100 meters depth at station 2 from 27 November 1978 to 22 January 1979. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.



Figure 39. Progressive vector diagram for the current meter at 175 meters depth at station 2 from 27 November 1978 to 22 January 1979. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.



Figure 40. Progressive vector diagram for the current meter at 300 meters depth at station 2 from 27 November 1978 to 22 January 1979. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.



Figure 41. Progressive vector diagram for the current meter at 140 meters depth at station 5 from 27 November 1978 to 22 January 1979. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.



Figure 42. Progressive vector diagram for the current meter at 215 meters depth at station 5 from 27 November 1978 to 22 January 1979. Crosses are positioned at 3 day intervals. Vertical axis indicates Magnetic North.

V. COMPARISON OF GEOSTROPHY WITH DIRECT CURRENT MEASUREMENTS

The two methods of inferring currents, indirect (geostrophy) and direct (current metering) coincided on 27 November 1978 and 8 January 1979. There were vertical profiling for watermass properties on the Cape San Martin line and simultaneous direct measurements at stations 2 and 5 of that line.

The mean velocity from the current meters was found for a 24-hour period bracketing the time during which watermass properties were sampled. This was accomplished by computing: $\vec{V}(t) = \frac{\vec{R}(t+12) - \vec{R}(t-12)}{24}$ where $\vec{R}$ is the position vector at the given time taken from a list of the values used to produce the progressive vector diagram. This 24-hour averaging was done so as to smooth the high frequency non-geostrophic contributions to the flow while retaining larger scales. It must be expected that this averaging process does not smooth out all non-geostrophic components. Those which remain contribute to differences between the direct (current meter) and indirect (geostrophic) velocity measurements.

The mean metered velocities at stations 2 and 5 on both 27 November 1978 and 8 January 1979 are compared to those velocities found by geostrophy in Table II.

As seen in Table II, on 27 November 1978 at station 2, there is general agreement on the direct and indirect measurement of velocities at 100 and 175 meters. At 300 meters the

methods of measurement indicate opposite flow directions. Dynamic topography indicates the region to be fairly flat with adjacent northward flow. The current meter shows a moderate southward flow of 10 cm/sec. This bottom meter is the meter which showed obvious non-geostrophic components, frequent oscillations between northward and southward flow. On the same data at station 5, the table shows strong agreement between the two methods of measurement. Geostrophy indicates a slightly stronger flow and the current meters show more of an onshore flow.

On 8 January 1979 at station 2, there is poor correlation of the current from the two measurement methods. Geostrophy indicates the region, at mid and lower depths, to be fairly flat with weak flow. Direction can only be inferred from that at station 4 (Figures 19 and 20). At the 100 meter level the current meter shows an onshore southward flow while geostrophy indicates northward flow parallel to the coast. At station 5 one can see reasonable agreement between the two methods of measurement (Table II). Current meters show uniform speed with depth and geostrophy indicates weakening of the flow with depth.

In summary there is general agreement between the two methods of measurement. It must be remembered that geostrophic calculations for station 2 were based on extrapolations and to that extent are uncertain. Further, the averaging of the current over 24 hours does not remove all non-geostrophic components, especially in the periods of

strong fluctuations. The geostrophic current, as expected, is a more useful estimate of the flow in this variable regime during the relatively quiet (i.e., steady) flow periods.

VI. CONCLUSIONS

In summarizing the current and watermass variations, the time interval between cruises is used for an initial breakdown. Currents are described by geostrophy at the time of each cruise and by current meter measurements during the intervals. Watermass properties are known only at cruise times.

From 27 November 1978 to 8 January 1979, near the level of 100 meters, there is an increased halocline slope downward toward the coast and an intense northward flow spreading westward. This spreading flow also occurs at 200 and 300 meters. Below 300 meters, southward flow develops. A salinity maximum at 300 meters occurs near the center of the station lines in November and at the western edge in early January.

From 8 January 1979 to 22 January 1979 the halocline levels off and becomes less intense. At 100 meters the northward flow has weakened and at 200 meters remains unchanged. From 300 to 500 meters there is a reduction in salinity due to horizontal advection, vice vertical, of low salinity water. There is also reduced southward flow below 300 meters during this interval.

These results by indirect measurements are consistent with direct (current meters) methods. At 100 meters northward flow spreads westward from 27 November 1978 to 22

January 1979. At about 1 January this flow shows an increased westward component, i.e. it crosses contours into deeper water. Vertical extent of the northward flow also increases during this period. Southward flow is present at mid-depth until 6 December when it turns northward at both stations 2 and 5. At 300 meters, a frontal region separating northward and southward flow, the flow is southward until early December when much oscillating dominates the rest of the period.

Indications are that the flow is branched and northward at the surface, consistent with Wickham's (1975) findings farther north. Presence of a surface maximum, Davidson Current, during the winter is almost universally consistent with the observations of other investigators. Westward propagation of the flow tends to support McCreary's (1977) model.

From 22 January 1979 to 21 February 1979 there is an increase in salinity at all levels. The northward jet shows further westward movement.

Measurement of the currents is still in progress. A 3-meter array was installed farther west at station 7 and in April 1979 was increased to a 4-meter array. Arrays are also being maintained at stations 2 and 5. Along with current meter measurements, simultaneous measurements of watermass properties are made at regular intervals.

TABLE II

COMPARISON OF CURRENT METER AND GEOSTROPHIC CURRENT VELOCITIES ON 27 NOVEMBER 1978 AND 8 JANUARY 1979

Date	Station	Depth (meters)	Current Meters θ(1) direction (ref. Mag N)	Current Meters V(1) (cm/sec)	Geostrophy θ(2) direction (ref. Mag N)	Geostrophy V(3) (cm/sec)
27 November	2	100	331°	16.2	310°	strong
		175	352°	2.9	305°	moderate
		300	112°	10.0	335°	weak
27 November	5	140	337°	9.5	310°	15.1
		215	339°	4.7	305°	9.1
8 January	2	100	076°	4.8	310°	strong
		175	249°	6.8	variable	weak
		300	332°	38.3	variable	weak
8 January	5	140	300°	16.6	310°	25.1
		215	240°	16.9	285°	weak

NOTES

(1) θ and V (current Meters) found using $\frac{\vec{R}(t+12) - \vec{R}(t-12)}{24}$ where $\vec{R}$ is the position vector at the given time taken from a list of values used to produce the progressive vector diagram.

(2) θ (geostrophy) found from dynamic topographies.

(3) V (geostrophy) $V = \frac{V_n}{\cos \theta}$ where V_n is the normal component of velocity from geostrophic cross sections and θ is the angle from the normal.

```
C     PROGRAM NOYFB                                                          NY000010
C                                                                            NY000020
C     PROGRAM NYOFB, REVISED VERSION OF:                                     NY000030
C     REVISION 9.1, MARCH 1975                                               NY000040
C     REVISED OCTOBER 1978 BY K. CODDINGTON                                  NY000050
C     FOR USE WITH IBM 360 COMPUTER                                          NY000060
C     WRITTEN IN FORTRAN IV LANGUANGE                                        NY000070
C     REQUIRES SUBROUTINES CALC,CONST,TRANS,PTIO                             NY000080
C     REQUIRES FUNCTION JCD                                                  NY000090
C                                                                            NY000100
C     DETERMINES THE STATIC CONFIGURATION OF SUB-SURFACE                     NY000110
C     MOORINGS WHEN ACTED UPON BY NON-COPLANAR CURRENT PROFILES              NY000120
C                                                                            NY000130
C                                                                            NY000140
C     MAIN PROGRAM CONTROLS I/O AND OPTION SELECTION                         NY000150
C     SENSE SWITCH OPTIONS ARE INDICATED BY ISSW(I) WHERE 1=ON AND 2=OFF     NY000160
C     S.S. - 1 - ON - LIST INPUT PARAMETERS                                  NY000170
C          - 2 - ON - OUTPUT SEGMENT STATS                                   NY000180
C          - 3 - ON - OUTPUT SUPPLEMENTAL STATS                              NY000190
C          - 4 - ON - OUTPUT SUMMARY MOORING STATISTICS                      NY000200
C          - 5 - ON - OUTPUT COMPONENT CHARACTERISTICS                       NY000210
C          -10 - ON - OUTPUT TO SOFT COPY DEVICE                             NY000220
C          -10 - OFF- OUTPUT TO HARD COPY DEVICE                             NY000230
C          -14 - ON - ABORT RUN - GO TO 'PAUSE'                              NY000240
C                                                                            NY000250
      COMMON W(42),A(42),RBS(24),AW(5),E(16)                                 NY000260
      COMMON IT(65),XL(65),TW(66),CDN(5),CDT(5)                              NY000270
      COMMON DCP(20),CP(20),RCP(20),IHDG(36)                                 NY000280
      COMMON T1(65),T2(65),T3(65),T4(65),T5(65),T6(65),T7(65)                NY000290
      COMMON IDA(10),IDM(10),DB(10)                                          NY000300
      COMMON DPT,QN200,D200,FPM,LI1,LC,LC3,NEW,TERMW,TERML                   NY000310
      COMMON RD,PI,TL,IC,IV,FUDG,RC,SEG,DONE                                 NY000320
      COMMON TCLIN,TTENS,TROTN,QBKUP,TVELO,ANCR,ANCRA                        NY000330
      COMMON ISSW(14)                                                        NY000340
      ISSW(1)=1                                                              NY000350
      ISSW(2)=1                                                              NY000360
      ISSW(3)=1                                                              NY000370
      ISSW(4)=1                                                              NY000380
      ISSW(5)=1                                                              NY000390
      ISSW(6)=1                                                              NY000400
      ISSW(7)=1                                                              NY000410
      ISSW(8)=1                                                              NY000420
      ISSW(9)=1                                                              NY000430
      ISSW(10)=1                                                             NY000440
      ISSW(11)=0                                                             NY000450
      ISSW(12)=0                                                             NY000460
      ISSW(13)=0                                                             NY000470
      ISSW(14)=0                                                             NY000480
```

```
      DATA IBLANK/'     '/                                                    NY000490
      LL = 0                                                                  NY000500
      IC = 0                                                                  NY000510
      NEW = 15                                                                NY000520
      ISLEW = IBLANK                                                          NY000530
C                                                                             NY000540
CC    SET STANDARD WHOI COMPONENT CONSTANTS                                   NY000550
C                                                                             NY000560
      CALL CONST                                                              NY000570
C                                                                             NY000580
CC    ENTER I/O UNIT REFERENCE NUMBERS                                        NY000590
CC    STANDARD U.R.N. FOR WHOI/BUOY COMPUTER ARE LISTED                       NY000600
C                                                                             NY000610
      WRITE (6,1)                                                             NY000620
1     FORMAT ('0ENTER FIVE I/O DEVICES',/,' SOFT COPY,HARD COPY,PAPER PUNY000630
     1NCH,KEYBOARD,PAPER READER',/,' STANDARD URN ARE: 6,8,2,5,2')            NY000640
      READ (5,600) LO1, LO2, LO3, LI, LI1                                     NY000650
600   FORMAT (5I1)                                                            NY000660
      WRITE (LO1,46)                                                          NY000670
   46 FORMAT ('0INITIAL RUN FROM P.T.?: 1-YES, 0-NO')                         NY000680
      READ (LI, 601) I                                                        NY000690
601   FORMAT (I2)                                                             NY000700
      IF (I-1) 59,55,55                                                       NY000710
C                                                                             NY000720
CC    INPUT MOORING COMPONENTS AND CONSTANTS FROM PAPER                       NY000730
C     TAPE OR OTHER SOURCE                                                    NY000740
C                                                                             NY000750
   55 CALL PTIO                                                               NY000760
      WRITE (LO1,51) DPT                                                      NY000770
   51 FORMAT (F6.1)                                                           NY000780
      LL = 0                                                                  NY000790
      GO TO 105                                                               NY000800
C                                                                             NY000810
CC    THE FOLLOWING SECTION PERMITS INPUT OF VARIABLE                         NY000820
CC    PARAMETERS FOR THE INITIAL AND SUBSEQUENT RUNS                          NY000830
CC    FORMAT STATEMENTS DESCRIBE THE OPERATIONS                               NY000840
C                                                                             NY000850
   59 CONTINUE                                                                NY000860
   60 WRITE (LO1,2)                                                           NY000870
    2 FORMAT ('0CHANGE COMP. CONSTANTS?: 1-YES,0-NO')                         NY000880
      READ (LI, 602) I                                                        NY000890
602   FORMAT (I2)                                                             NY000900
      IF (I-1) 75,61,61                                                       NY000910
   61 WRITE (LO1,3)                                                           NY000920
62    READ (LI, 603) I,J,X                                                    NY000930
3     FORMAT ('0ENTER CODING:1-W(I),2-A(I),3-RBS(I),4-AW(I)',/,' THEN TYNY000940
     1PE COMPONENT CODE NO. AND NEW VALUE')                                   NY000950
603   FORMAT (I2, 1X, I2, F10.5)                                              NY000960
```

```
   63 GO TO (65,66,67,68,70), I                                          NY000970
   65 W(J) = X                                                           NY000980
      GO TO 69                                                           NY000990
   66 A(J) = X                                                           NY001000
      GO TO 69                                                           NY001010
   67 RBS(J) = X                                                         NY001020
      GO TO 69                                                           NY001030
   68 AW(J) = X                                                          NY001040
   69 WRITE (LO1,700)                                                    NY001050
700   FORMAT ('ONEXT OR 05')                                             NY001060
    4 FORMAT ('ONEXT OR 99')                                            NY001070
      GO TO 62                                                          NY001080
   70 IF (LL-1) 75,340,340                                              NY001090
   75 WRITE (LO1,5)                                                     NY001100
    5 FORMAT ('OCHANGE STRETCH CHARACTERISTICS?: 1-YES, 0-NO')          NY001110
      READ (LI, 604) I                                                  NY001120
604   FORMAT (I2)                                                       NY001130
      IF (I-1) 151,76,76                                                NY001140
   76 WRITE (LO1,6)                                                     NY001150
    6 FORMAT ('0ENTER: 1-WIRE, 2-DACRON, 3-NYLON, 4-UNSPEC.')           NY001160
77    READ (LI, 605) I                                                  NY001170
605   FORMAT (I2)                                                       NY001180
      IF (I-99) 78,80,80                                                NY001190
   78 WRITE (LO1,7)                                                     NY001200
    7 FORMAT ('ONOW ENTER THE 4 CONSTANTS')                             NY001210
      I = I*4-3                                                         NY001220
      READ (LI, 606) E(I), E(I+1), E(I+2), E(I+3)                       NY001230
606   FORMAT (4E12.5)                                                   NY001240
      WRITE (LO1,4)                                                     NY001250
      GO TO 77                                                          NY001260
   80 IF (LL-1) 151,340,340                                             NY001270
C                                                                       NY001280
C     'I2' IS THE COUNTER FOR INSERT AND DELETE                         NY001290
C                                                                       NY001300
  150 WRITE (LO1,8)                                                     NY001310
    8 FORMAT ('OTYPE 1-CHANGE, 2-INSERT, 3-DELETION THEN')              NY001320
  151 WRITE (LO1,9)                                                     NY001330
    9 FORMAT ('OMOORING COMP. NO., TYPE, LENGTH OR NO. OF BALLS')       NY001340
      I2 = 0                                                            NY001350
  153 IF (LL-1) 158,155,155                                             NY001360
155   READ (LI, 607) N,I,J,X                                            NY001370
607   FORMAT (I2,1X,I2,1X,I2,1X,F10.5)                                  NY001380
      GO TO (850,180,190,340),N                                         NY001390
158   READ (LI,608) I,J,X                                               NY001400
608   FORMAT (I2,1X,I2,1X,F10.5)                                        NY001410
      IF (I-99) 160,92,92                                               NY001420
  160 IC = I                                                            NY001430
  175 II = I+I2                                                         NY001440
```

```
      IT(I1) = J                                                        NY001450
      XL(I1) = X                                                        NY001460
      GO TO 195                                                         NY001470
C                                                                       NY001480
CC    CHANGE COMPONENT                                                  NY001490
C                                                                       NY001500
850   I1=I+I2                                                           NY001510
      IT(I1)=J                                                          NY001520
      XL(I1)=X                                                          NY001530
      GO TO 810                                                         NY001540
C                                                                       NY001550
CC    INSERT COMPONENT                                                  NY001560
C                                                                       NY001570
  180 I1 = IC                                                           NY001580
  182 IF (I1-(I+I2)) 186,186,184                                        NY001590
  184 XL(I1+1) = XL(I1)                                                 NY001600
      IT(I1+1) = IT(I1)                                                 NY001610
      I1 = I1-1                                                         NY001620
      GO TO 182                                                         NY001630
  186 XL(I1+1) = X                                                      NY001640
      IT(I1+1) = J                                                      NY001650
      IC = IC+1                                                         NY001660
      I2 = I2+1                                                         NY001670
      GO TO 810                                                         NY001680
C                                                                       NY001690
CC    DELETE COMPONENT                                                  NY001700
C                                                                       NY001710
  190 I3 = I+I2                                                         NY001720
      I4 = IC-1                                                         NY001730
      DO 192 I1 = I3,I4                                                 NY001740
      XL(I1) = XL(I1+1)                                                 NY001750
      IT(I1) = IT(I1+1)                                                 NY001760
  192 CONTINUE                                                          NY001770
      IC = IC-1                                                         NY001780
      I2 = I2-1                                                         NY001790
810   WRITE (LO1,811)                                                   NY001800
811   FORMAT ('ONEXT OR 04')                                            NY001810
      GO TO 153                                                         NY001820
  195 WRITE (LO1,4)                                                     NY001830
      GO TO 153                                                         NY001840
197   IF (LL-1) 92,340,340                                              NY001850
   92 WRITE (LO1,10)                                                    NY001860
   10 FORMAT ('OLINE MEASURED AT 200(D)SQR?: 1-YES, 0-NO')              NY001870
      READ (LI,609) I                                                   NY001880
609   FORMAT (I2)                                                       NY001890
      IF (I-1) 95,94,94                                                 NY001900
   94 ON200 = 1.0                                                       NY001910
      D200 = 1.0                                                        NY001920
```

```
      GO TO 96                                                          NY001930
   95 QN200 = 1.042                                                     NY001940
      D200 = 1.032                                                      NY001950
   96 IF (LL-1) 98,340,340                                              NY001960
   98 WRITE (LO1,11)                                                    NY001970
   11 FORMAT ('0ENTER ANCHOR WT.(+LBS), AREA((M)SQR)')                  NY001980
      READ (LI,610) ANCR, ANCRA                                         NY001990
610   FORMAT (F7.2, F5.2)                                               NY002000
      IF (LL-1) 215,340,340                                             NY002010
  215 WRITE (LO1,19)                                                    NY002020
   19 FORMAT ('0ENTER COMMENTS - 1 LINE MAX.')                          NY002030
C                                                                       NY002040
C     SET 'COMMENT' ARRAY TO BLANKS                                     NY002050
C                                                                       NY002060
      DO 217 K = 1,36                                                   NY002070
      IHDG(K)= IBLANK                                                   NY002080
  217 CONTINUE                                                          NY002090
      READ (LI,35) (IHDG(K),K = 1,36)                                   NY002100
   35 FORMAT (36(A2))                                                   NY002110
      IF (LL-1) 100,340,340                                             NY002120
  100 WRITE (LO1,41)                                                    NY002130
   41 FORMAT ('0ENTER: DEPTH OF WATER (METERS)')                        NY002140
      READ (LI,611) DPT                                                 NY002150
611   FORMAT (F6.1)                                                     NY002160
  105 CONTINUE                                                          NY002170
  110 IV = 1                                                            NY002180
      WRITE (LO1,12)                                                    NY002190
12    FORMAT ('0INPUT CURRENT PROFILE--DEPTH(METERS),SPEED(CM/SEC),DIREC NY002200
     1TION(DEGR)')                                                      NY002210
112   READ (LI,612) DCP(IV), CP(IV), RCP(IV)                            NY002220
612   FORMAT (F6.1,1X,F4.1,1X,F5.1)                                     NY002230
      IV = IV +1                                                        NY002240
      IF (DCP(IV-1)-DPT) 112,115,115                                    NY002250
  115 IV = IV-1                                                         NY002260
      IF (LL-1) 120,340,340                                             NY002270
  120 WRITE (LO1,13)                                                    NY002280
   13 FORMAT ('0CHANGE STANDARD CD?: 1-YES, 0-NO')                      NY002290
      READ (LI,613) I                                                   NY002300
613   FORMAT (I2)                                                       NY002310
      IF (I-1) 130,122,122                                              NY002320
  122 WRITE (LO1,14)                                                    NY002330
   14 FORMAT ('0ENTER: 1-WIRE,2-LINE,3-INSTR,4-BALLS,5-UNSPEC.   THEN CD(NY002340
     1N),CD(T)')                                                        NY002350
123   READ (LI,614) I,X,Y                                               NY002360
614   FORMAT (I2,1X,F3.1,1X,F6.3)                                       NY002370
      IF ( I-99) 124,127,127                                            NY002380
  124 CDN(I) = X                                                        NY002390
      CDT(I) = Y                                                        NY002400
```

```
      IF (I-4) 126,125,126                                                  NY002410
C                                                                           NY002420
C     Y/PI FOR CDT OF SPHERES ALLOWS USE OF THE                             NY002430
C     EQUATION FOR THE TANGENTIAL DRAG OF CYLINDERS                         NY002440
C                                                                           NY002450
  125 CDT(I) = Y/PI                                                         NY002460
  126 WRITE (LO1,4)                                                         NY002470
      GO TO 123                                                             NY002480
  127 IF (LL-1) 130,340,340                                                 NY002490
  130 WRITE (LO1,15)                                                        NY002500
   15 FORMAT ('0SEGMENT LENGTH(METERS)?')                                   NY002510
      READ (LI,615) SEG                                                     NY002520
615   FORMAT (F7.2)                                                         NY002530
      IF (LL-1) 200,340,340                                                 NY002540
  200 WRITE (LO1,16)                                                        NY002550
   16 FORMAT ('0AUTO LENGTH ADJUST?:-0 TO 10 COMPONENTS')                   NY002560
      READ (LI,616) IDZ                                                     NY002570
616   FORMAT (I2)                                                           NY002580
      IF (IDZ.EQ.0) GO TO 206                                               NY002590
  202 WRITE (LO1,17)                                                        NY002600
   17 FORMAT ('0ENTER: CRITICAL COMP., DESIRED DEPTH, ADJUST. COMP.')       NY002610
      DO 204 I = 1,IDZ                                                      NY002620
      READ (LI,617) IDA(I), DB(I), IDM(I)                                   NY002630
617   FORMAT (I2,1X,F6.1,1X,I2)                                             NY002640
  204 CONTINUE                                                              NY002650
  206 IF (LL-1) 210,340,340                                                 NY002660
  210 WRITE (LO1,18)                                                        NY002670
   18 FORMAT ('0ENTER MAGNITUDE, INCLINATION,AZIMUTH OF P.F.')              NY002680
      READ (LI,618) TTENS,TCLIN,TROTN                                       NY002690
618   FORMAT (3F5.1)                                                        NY002700
      IF (LL-1) 211,340,340                                                 NY002710
  211 WRITE (LO1,42)                                                        NY002720
   42 FORMAT ('0CHANGE IN TERMINATION CONSTANTS?: 1-YES, 0-NO')             NY002730
      READ (LI,619) I                                                       NY002740
619   FORMAT (I2)                                                           NY002750
      IF (I-1) 213,212,212                                                  NY002760
  212 WRITE (LO1,43)                                                        NY002770
   43 FORMAT ('0ENTER TERM. LENGTH(METER),WT.(LBS)')                        NY002780
      READ (LI,620) TERML,TERMW                                             NY002790
620   FORMAT (F6.3,1X,F6.3)                                                 NY002800
C     SET LL=2: INDICATES INITIALIZATION COMPLETE                           NY002810
213   LL=1                                                                  NY002820
      GO TO 340                                                             NY002830
C                                                                           NY002840
C     START NEW COMPUTATION                                                 NY002850
C     RESET CRITICAL VARIABLES TO 0.0                                       NY002860
C                                                                           NY002870
  220 CONTINUE                                                              NY002880
```

```
      TW(1) = 0.0                                                       NY002890
      TL = 0.0                                                          NY002900
      BKUP = 0.0                                                        NY002910
      DONE = 0.0                                                        NY002920
C                                                                       NY002930
CC    CALCULATE LAUNCH TRANSIENTS                                       NY002940
C                                                                       NY002950
      CALL TRANS                                                        NY002960
      RC = DPT-TL                                                       NY002970
      FUDG = 0.0                                                        NY002980
C                                                                       NY002990
CC    SET HARD / SOFT COPY DEVICE FOR OUTPUT                            NY003000
C                                                                       NY003010
  244 IF (DONE-1.0) 255,245,245                                         NY003020
  245 LO = LO1                                                          NY003030
      IF (ISSW(10)) 247,246,247                                         NY003040
  246 LO = LO2                                                          NY003050
C                                                                       NY003060
CC    WRITE INPUT PARAMETERS                                            NY003070
CC    WRITE HEADING                                                     NY003080
CC    'ISLEW' ADVANCES PAGE TO NEW SHEET                                NY003090
C                                                                       NY003100
  247 IF (ISSW(1)) 248,253,248                                          NY003110
  248 WRITE (LO,20) ISLEW                                               NY003120
20    FORMAT (1H1)                                                      NY003130
      WRITE (LO,35) (IHDG(K),K = 1,36)                                  NY003140
      WRITE (LO,21) (CDN(I),I = 1,5),(CDT(J),J = 1,5)                   NY003150
   21 FORMAT (/20X,17H INPUT PARAMETERS//16X,18H DRAG COEFFICIENTS      NY003160
     1/10X,43H WIRE     LINE    CYLIND   SPHERE   UNSPEC.               NY003170
     2/6H CD(N),5(4X,F5.3),/6H CD(T),5(4X,F5.3))                        NY003180
      WRITE (LO,22) DPT,ANCR,TTENS,ANCRA,TCLIN,TVELO,                   NY003190
     1TROTN,SEG,TERMW,TERML                                             NY003200
22    FORMAT ('0WATER DEPTH',6X,F6.1,9X,'ANCHOR WT. (LBS)', 7X,F7.1,/, 'NY003210
     10P.F.MAGNITUDE',4X,F7.2,8X,'ANCHOR AREA',15X,F5.2,/,'0P.F.INCLINATNY003220
     2ION ',1X,F7.2,8X,'TERM.VELO.(M/MIN)',8X,F5.1,/,'0P.F.AZIMUTH',6X, NY003230
     3F7.2,8X,'SEGMENT LENGTH',10X,F6.1,/,'0TERM.WT',11X,F7.3,7X,'TERM.LNY003240
     4ENGTH',15X,F5.3)                                                  NY003250
      WRITE (LO,23)                                                     NY003260
   23 FORMAT (//6X,16H CURRENT PROFILE/                                 NY003270
     132H  DEPTH       SPEED     DIRECTION)                            NY003280
      DO 250 I = 1,IV                                                   NY003290
      WRITE  (LO,24) DCP(I),CP(I),RCP(I)                                NY003300
   24 FORMAT (1X,F6.1,2X,F5.1,7H CM-SEC,2X,F5.1,4H DEG)                 NY003310
  250 CONTINUE                                                          NY003320
C                                                                       NY003330
CC    WRITE HEADING FOR SEGMENT STATS. IF SS-2 IS ON                    NY003340
C     AND REENTER SJB. CALC                                             NY003350
C                                                                       NY003360
```

```
  253 IF (ISSW(1)) 254,269,254                                          NY003370
  254 WRITE (LO,20) ISLEW                                               NY003380
      WRITE (LO,35) (IHDG(K),K = 1,36)                                  NY003390
      WRITE (LO,33)                                                     NY003400
   33 FORMAT (//28X,18HSEGMENT STATISTICS )                             NY003410
      WRITE (LO,34)                                                     NY003420
34    FORMAT (//' COMP TYPE LENGTH INCL XEXC. YEXC. C.SPD C.DIR M.AZI UDNY003430
     1RAG VDRAG TDRAG')                                                 NY003440
C                                                                       NY003450
CC    SUBROUTINE CALC PERFORMS ALL BASIC CALCULATIONS                   NY003460
C                                                                       NY003470
  255 CALL CALC                                                         NY003480
      IF (ISSW(14)) 320,257,320                                         NY003490
C                                                                       NY003500
CC    CHECK DIFFERENCE BETWEEN ASSUMED DEPTH(RC) AND THE                NY003510
CC    CALCULATED DEPTH OF THE TOP COMPONENT. LESS THAN 2.0 M.?          NY003520
CC    IF YES - CHECK AUTO ADJUST STATUS,                                NY003530
CC    IF NO  - CALC NEW FUDG, SET NEW RC.                               NY003540
CC    (X-RC)*0.7 TO HASTEN CONVERGENCE IN LARGE CURRENT SHEER           NY003550
C                                                                       NY003560
  257 IF (DONE-1.0) 258,269,269                                         NY003570
  258 X = DPT-T4(IC)                                                    NY003580
      IF (ABS(RC-X)-2.0) 260,259,259                                    NY003590
  259 FUDG = FUDG+(X-RC)*0.7                                            NY003600
      RC = (DPT-TL)+FUDG                                                NY003610
      GO TO 255                                                         NY003620
C                                                                       NY003630
CC    AUTO ADJUST EVALUATION - CHECK SPECIFIED INSTRUMENT               NY003640
CC    DEPTHS,  IF AT DESIRED DEPTHS - SET (DONE=2.0) AND                NY003650
CC    GO TO OUTPUT,  IF DEPTHS ARE INCORRECT - ADJUST                   NY003660
CC    LENGTH OF (IDM) AND GO TO (220)                                   NY003670
C                                                                       NY003680
  260 IF (IDZ-1) 266,261,261                                            NY003690
261   DO 264 K = 1,IDZ                                                  NY003700
C                                                                       NY003710
CC    CHECK AND ADJUST LOWEST ELEMENTS FIRST                            NY003720
C                                                                       NY003730
      J = (IDZ-K)+1                                                     NY003740
      I = IDA(J)                                                        NY003750
      Z = ((DPT-T4(IC))+T4(I))-DB(J)                                    NY003760
      IF (ABS(Z)-1.0) 264,262,262                                       NY003770
  262 I = IDM(J)                                                        NY003780
C                                                                       NY003790
CC    99% OF Z TO PARTIALLY ALLOW FOR STRETCH                           NY003800
C                                                                       NY003810
      XL(I) = XL(I)+Z*0.99                                              NY003820
      GO TO 220                                                         NY003830
  264 CONTINUE                                                          NY003840
```

```
  266 DONE = 2.0                                                          NY003850
      GO TO 245                                                           NY003860
C                                                                         NY003870
CC    IF SS-4 ON OUTPUT SUMMARY OF MOOR. STATS.                           NY003880
C                                                                         NY003890
  269 IF (ISSW(4)) 271,281,271                                            NY003900
  271 WRITE (LO,20) ISLEW                                                 NY003910
      WRITE (LO,35) (IHDG(K),K = 1,36)                                    NY003920
  272 WRITE (LO,25)                                                       NY003930
   25 FORMAT (22X,28HMOORING STATISTICS - SUMMARY                         NY003940
     1//' COMP TYPE LENGTH  WEIGHT  DEPTH  INCLIN TENSION  EXCUR  DRAG BNY003950
     2ACK-UP')                                                            NY003960
      IBKUP = 0                                                           NY003970
      BKUP = QBKUP                                                        NY003980
      DO 280 K = 1,IC                                                     NY003990
      I1 = IT(K)                                                          NY004000
      IF (IBKUP) 274,274,273                                              NY004010
  273 BKUP = 0.0                                                          NY004020
      GO TO 276                                                           NY004030
  274 BKUP = BKUP-(XL(K)*W(I1)+TERMW)                                     NY004040
      IF (IT(K)-35) 276,275,276                                           NY004050
  275 IBKUP = 2                                                           NY004060
  276 QW = XL(K)*W(I1)                                                    NY004070
      QX = (DPT-T4(IC))+T4(K)                                             NY004080
      QY = SQRT((T5(IC)-T5(K))**2+(T6(IC)-T6(K))**2)                      NY004090
      WRITE (LO,26) K,IT(K),XL(K),QW,QX,T2(K),                            NY004100
     1T3(K),QY,T1(K),BKUP                                                 NY004110
   26 FORMAT (I4,3X,I2,2X,F6.1,1X,F7.1,2X,F6.1,1X,                        NY004120
     1F5.1,3X,F6.1,1X,F6.1,1X,F5.1,1X,F7.1)                               NY004130
      IF (ISSW(14)) 320,280,320                                           NY004140
  280 CONTINUE                                                            NY004150
C                                                                         NY004160
CC    IF SS-3 ON OUTPUT SUPPLEMENTAL STATISTICS                           NY004170
C                                                                         NY004180
  281 IF (ISSW(3)) 282,291,282                                            NY004190
  282 WRITE (LO,20) ISLEW                                                 NY004200
      WRITE (LO,35) (IHDG(K),K = 1,36)                                    NY004210
      WRITE (LO,27)                                                       NY004220
   27 FORMAT (/24X,23HSUPPLEMENTAL STATISTICS                             NY004230
     1//39H COMP TYPE CD(N)  AREA  STR.LT PERC.STR                        NY004240
     232H  S.F. XEXCUR YEXCUR LAUNCH TENS )                               NY004250
      DO 290 K = 1, IC                                                    NY004260
      I1 = IT(K)                                                          NY004270
      J1 = JCD(I1)                                                        NY004280
      IF (IT(K)-25) 283,284,284                                           NY004290
  283 QR = RBS(I1)/T3(K-1)                                                NY004300
      GO TO 285                                                           NY004310
  284 QR = 0.0                                                            NY004320
```

```
  285 QA = XL(K)*A(I1)                                                    NY004330
      QS = (T7(K)/XL(K))*100.0                                            NY004340
      QSL = T7(K)+XL(K)                                                   NY004350
      QX = T5(IC)-T5(K)                                                   NY004360
      QY = T6(IC)-T6(K)                                                   NY004370
      WRITE (LO,28) K, IT(K),CON(J1),QA,QSL,QS,QR,                        NY004380
     1QX,QY,TW(K)                                                         NY004390
   28 FORMAT (I4,3X,I2,3X,F3.1,1X,F6.3,2X,F6.1,3X,F5.2,3X,                NY004400
     1F5.1,F7.1,F7.1,3X,F6.1)                                             NY004410
  290 CONTINUE                                                            NY004420
C                                                                         NY004430
CC    IF SS-5 ON OUTPUT COMPONENT CHARACTERISTICS                         NY004440
C                                                                         NY004450
  291 IF (ISSW(5)) 292,320,292                                            NY004460
  292 WRITE (LO,20) ISLEW                                                 NY004470
      WRITE (LO,35) (IHDG(K),K = 1,36)                                    NY004480
      WRITE (LO,47)                                                       NY004490
   47 FORMAT (/16X,26H COMPONENT CHARACTERISTICS                          NY004500
     2//' COMP TYPE LENGTH      A(I)     W(I)    RBS(I)    AW(I)')       NY004510
      DO 300 K = 1,IC                                                     NY004520
      I1 = IT(K)                                                          NY004530
      X = 0.0                                                             NY004540
      Y = 0.0                                                             NY004550
      IF (IT(K)-6) 293,294,294                                            NY004560
  293 X = AW(I1)                                                          NY004570
  294 IF (IT(K)-25) 295,296,296                                           NY004580
  295 Y = RBS(I1)                                                         NY004590
  296 WRITE (LO,48) K, IT(K),XL(K),A(I1),W(I1),Y,X                        NY004600
   48 FORMAT (I4,3X,I2,2X,F6.1,1X,F9.7,1X,F9.5,1X,F7.1,1X,F8.6)           NY004610
      IF (ISSW(14)) 320,300,320                                           NY004620
  300 CONTINUE                                                            NY004630
      WRITE (LO,49) (E(I),I = 1,16)                                       NY004640
   49 FORMAT (//19X,18H STRETCH CONSTANTS                                 NY004650
     1/2X,6H COMP.,8X,3H(1),10X,3H(2),10X,3H(3),10X,3H(4),                NY004660
     2/,' ( 1 -  5)',4(E13.5),/,' ( 6 - 10)',4(E13.5),/,' (11 - 15)',4(ENY004670
     313.5),/,' (16 - 20)',4(E13.5))                                      NY004680
C                                                                         NY004690
CC    END OF RUN                                                          NY004700
CC    'PAUSE' TO THINK, IF SO INCLINED                                    NY004710
CC    WRITE OPTIONS FOR POSSIBLE CHANGES                                  NY004720
C                                                                         NY004730
  320 CONTINUE                                                            NY004740
      WRITE (LO1,29)                                                      NY004750
29    FORMAT ('OPAUSE, RUN=22, END=99')                                   NY004760
      READ (LI,229) IDUMMY                                                NY004770
229   FORMAT (I2)                                                         NY004780
      IF (IDUMMY.EQ.99) GO TO 345                                         NY004790
  321 IDZ = 0                                                             NY004800
```

```
      WRITE (LO1,44)                                                    NYC04810
44    FORMAT ('OCHANGE OPTIONS',/,'0 1 COMP.CHAR.',/,'  2 STRETCH CHAR.'NY004820
     1,/,'  3 MOOR.CONFIGURATION',/,'  4 200(D)SOR MEASURE',/,'  5 ANCHONY004830
     2R WT.',/,'  6 WATER DEPTH',/,'  7 CURRENT PROFILE',/,'  8 DRAG COENY004840
     3FF',/,'  9 SEGMENT LENGTH',/,' 10 AUTO ADJUST STATUS',/,' 11 P.F. NY004850
     4AT TOP',/,' 12 TERM.CONST.',/,' 13 COMMENTS',/,' 14 CONTINUE W/O RNY004860
     5ECALC',/,' 15 INPUT MOOR.FROM PTR',/,' 16 OUTPUT MOOR.TO PP')     NY004870
323   READ (LI,621) NEW                                                 NY004880
621   FORMAT (I2)                                                       NY004890
C                                                                       NY004900
C     OPTION  1  2  3   4  5  6   7   8   9   10  11  12               NY004910
      GO TO (61,76,150,92,98,100,110,122,130,20C,210,212,               NY004920
     1215,245,55,336,220), NEW                                          NY004930
C       13  14  15  16  99                                              NY004940
CCC                                                                     NY004950
C                                                                       NY004960
C     OUTPUT EXISTING MOORING AND CONSTANTS TO PAPER TAPE               NY004970
C                                                                       NY004980
  336 CALL PTIO                                                         NY004990
  340 WRITE (LO1,31)                                                    NY005000
   31 FORMAT ('0GO? - (17) OR OPTION? - (1 TO 16)')                     NY005010
      GO TO 323                                                         NY005020
  345 CONTINUE                                                          NY005030
      STOP                                                              NY005040
      END                                                               NY005050
      SUBROUTINE CALC                                                   NY005060
C                                                                       NY005070
C     SUBROUTINE CALC - USE WITH PROG. NOYFB, REV. 9.1                  NY005080
C     CALCULATION TO DETERMINE ALL MOORING STATISTICS                   NY005090
C                                                                       NY005100
      COMMON W(42),A(42),RBS(24),AW(5),E(16)                            NY005110
      COMMON IT(65),XL(65),TW(66),CDN(5),CDT(5)                         NY005120
      COMMON DCP(20),CP(20),RCP(20),IHDG(36)                            NY005130
      COMMON T1(65),T2(65),T3(65),T4(65),T5(65),T6(65),T7(65)           NY005140
      COMMON IDA(10),IDM(10),DB(10)                                     NY005150
      COMMON DPT,ON200,D200,FPM,LII,LC,LC3,NEW,TERMW,TERML              NY005160
      COMMON RD,PI,TL,IC,IV,FUDG,RC,SEG,DONE                            NY005170
      COMMON TCLIN,TTENS,TROTN,QBKUP,TVELO,ANCR,ANCRA                   NY005180
      COMMON ISSW(14)                                                   NY005190
C                                                                       NY005200
C     RESET VARIABLES TO INITIALIZE                                     NY005210
C                                                                       NY005220
      TLD = DPT-TL                                                      NY005230
      DRAG = 0.0                                                        NY005240
      JC = 2                                                            NY005250
      TSTR = 0.0                                                        NY005260
      TVHT = 0.0                                                        NY005270
      CLIN = TCLIN*RD                                                   NY005280
```

```
      PCLIN = CLIN                                                          NY005290
      TENS = TTENS                                                          NY005300
      ROTN = TROTN*RD                                                       NY005310
      TXEX = 0.0                                                            NY005320
      TYEX = 0.0                                                            NY005330
      CPK = 1.076391E-01                                                    NY005340
C                                                                           NY005350
CCC   PRIMARY LOOP                                                          NY005360
C                                                                           NY005370
      DO 570 I = 1,IC                                                       NY005380
      I1 = IT(I)                                                            NY005390
C                                                                           NY005400
CCC   DETERMINE DRAG COEFF. SUBSCRIPT (FUNCTION JCD)                        NY005410
C                                                                           NY005420
      J1 = JCD(I1)                                                          NY005430
C                                                                           NY005440
CCC   DETERMINE NO. OF SEGMENTS IN COMPONENT (I)                            NY005450
C                                                                           NY005460
  500 L = 1+IFIX(XL(I)/SEG)                                                 NY005470
C                                                                           NY005480
CCC   SECONDARY LOOP FOR SEGMENT CALC.                                      NY005490
C                                                                           NY005500
  505 DO 562 K = 1,L                                                        NY005510
C                                                                           NY005520
CCCCC SET SEGMENT LENGTH (CLI) AND BUOYANCY (WT)                            NY005530
CCCCC CALC. CURRENT:- MEAN DEPTH (DN), SPEED(VN),                           NY005540
CCCCC DIRECTION(ROT), FOR EACH SEGMENT                                      NY005550
C                                                                           NY005560
      IF (K-L) 509,507,507                                                  NY005570
  507 CLI = (XL(I)-SEG*FLOAT(K-1))+TERML                                    NY005580
      WT = W(I1)*(CLI-TERML)+TERMW                                          NY005590
      GO TO 510                                                             NY005600
  509 CLI = SEG                                                             NY005610
      WT = W(I1)*SEG                                                        NY005620
  510 DN = TLD+(CLI/2.0)+FUDG*((DPT-(TLD+CLI/2.0))/TL)                      NY005630
C                                                                           NY005640
CCC   ASSIGN DEEPEST CURRENT VALUES IF DN EXCEEDS DPT                       NY005650
C                                                                           NY005660
      IF (DN-DPT) 514,512,512                                               NY005670
  512 VN = CP(IV)*CPK                                                       NY005680
      ROT = RCP(IV)*RD                                                      NY005690
      GO TO 519                                                             NY005700
  514 IF (DN-DCP(JC)) 518,516,516                                           NY005710
  516 JC = JC+1                                                             NY005720
      GO TO 514                                                             NY005730
  518 VN = (CP(JC-1)+(((DN-DCP(JC-1))/(DCP(JC)-DCP(JC-1)))                  NY005740
     1*(CP(JC)-CP(JC-1))))*CPK                                              NY005750
      ROT = (RCP(JC-1)+(((DN-DCP(JC-1))/(DCP(JC)-DCP(JC-1)))                NY005760
```

```
     1*(RCP(JC)-RCP(JC-1))))*RD                                                NY005770
C                                                                              NY005780
CC       SET ROTN=ROT WHEN TENSION = 0                                         NY005790
C                                                                              NY005800
  519 IF (TENS) 522,522,524                                                    NY005810
  522 ROTN = ROT                                                               NY005820
C                                                                              NY005830
CC       CALC. DRAG FORCES,TENSION,INCLINATION AND AZIMUTH OF SEG.             NY005840
CC       ITERATE UNTIL CHANGE LESS THAN 0.1 DEGREES FOR                        NY005850
CC       INCLINATION - LOOP 526 TO 530                                         NY005860
CC       MOORING AZIMUTH - LOOP 526 TO 527                                     NY005870
C                                                                              NY005880
  524 X = ROTN                                                                 NY005890
      Y = ROTN                                                                 NY005900
      Z = TENS*SIN(CLIN)                                                       NY005910
  526 QCLIN = PCLIN                                                            NY005920
      ANINC = QCLIN-CLIN                                                       NY005930
      UTVN = VN*COS(ROT-ROTN)                                                  NY005940
      VTVN = VN*SIN(ROT-ROTN)                                                  NY005950
      DRGT = A(I1)*PI*CLI*CDT(J1)*(SIN(QCLIN)*UTVN)*                           NY005960
     1(ABS(SIN(QCLIN)*UTVN))                                                   NY005970
      UDRGN = A(I1)*CLI*CDN(J1)*(COS(QCLIN)*UTVN)*                             NY005980
     1(ABS(COS(QCLIN)*UTVN))                                                   NY005990
      VDRGN = A(I1)*CLI*CDN(J1)*VTVN*ABS(VTVN)                                 NY006000
      WTT = WT*COS(QCLIN)                                                      NY006010
      WTN = WT*SIN(QCLIN)                                                      NY006020
      QTENS = TENS*COS(ANINC)+WTT+DRGT                                         NY006030
C                                                                              NY006040
CC       (-WTN) CHANGE SIGN OF WTN FOR CORRECT SENSE                           NY006050
C                                                                              NY006060
      PCLIN = ATAN ((UDRGN-WTN-TENS*SIN(ANINC))/QTENS)+QCLIN                   NY006070
C                                                                              NY006080
CC       AVOID /0.0 IN STATEMENT 523                                           NY006090
C                                                                              NY006100
      IF (QTENS*SIN(PCLIN)) 523,529,523                                        NY006110
  523 ROTN = ATAN((VDRGN-Z*SIN(X-Y))/(QTENS*SIN(PCLIN)))+X                     NY006120
  529 IF (ISSW(14)) 570,525,570                                                NY006130
C                                                                              NY006140
CC       ASSURE +PCLIN                                                         NY006150
C                                                                              NY006160
  525 IF (PCLIN) 531,530,527                                                   NY006170
C                                                                              NY006180
CC       RATE OF CHANGE IN AZIMUTH < 0.1 DEGREE?                               NY006190
C                                                                              NY006200
  527 IF (ABS(ABS(X)-ABS(ROTN))-(0.1*RD)) 530,528,528                          NY006210
  528 X = ROTN                                                                 NY006220
      GO TO 526                                                                NY006230
C                                                                              NY006240
```

```
C      RATE OF CHANGE IN INCLINATION < 0.1 DEGREE?                          NY006250
C                                                                           NY006260
530    IF (ABS(QCLIN-PCLIN)-(0.1*RD)) 532,526,526                           NY006270
C                                                                           NY006280
C      HANDLES 180 DEG. ROTATION OF AZIMUTH WHEN VDRGN = 0.0                NY006290
C                                                                           NY006300
  531  PCLIN = -PCLIN                                                       NY006310
       ROTN = ROTN+PI                                                       NY006320
       GO TO 524                                                            NY006330
  532  TENS = COS(PCLIN-CLIN)*TENS+WT*COS(PCLIN)+DRGT                       NY006340
       CLIN = PCLIN                                                         NY006350
C                                                                           NY006360
C      STRETCH CALC.: - J2 = 1 FOR WIRE (538)                               NY006370
C                            2 FOR DACRON (544)                             NY006380
C                            3 FOR NYLON (544)                              NY006390
C                            4 FOR UNSPECIFIED (544)                        NY006400
C                                                                           NY006410
       STRL = CLI                                                           NY006420
       ELT = 0.0                                                            NY006430
534    IF (I1-21) 536,554,554                                               NY006440
  536  J2 = ((I1-1)/5)+1                                                    NY006450
       IF (J2-2) 538,540,540                                                NY006460
  538  ELT = ((TENS/RBS(I1))*E(1))+(TENS/(E(2)*AW(I1)))                     NY006470
       GO TO 546                                                            NY006480
C                                                                           NY006490
C      INTERPOLATION BETWEEN TW(I)&TW(I-1) FOR LAUNCH TRANSIENTS            NY006500
C      FOR PERMANENT ELONGATION CALC.                                       NY006510
C      ELT = PERMANENT ELONGATION + ELASTIC ELONGATION                      NY006520
C                                                                           NY006530
  540  X = TW(I-1)+(((TW(I)-TW(I-1))/XL(I))*(SEG*FLOAT(K-1)+CLI))          NY006540
       IF (X-TENS) 542,544,544                                              NY006550
  542  X = TENS                                                             NY006560
  544  N =(J2-1)*4+1                                                        NY006570
       ELT = (((X/(E(N)*A(I1)**2))**E(N+1))+((TENS/                         NY006580
      1(E(N+2)*A(I1)**2))**E(N+3)))/100.0                                   NY006590
C                                                                           NY006600
C      CALC. SEGMENT STRETCHED LENGTH(STRL)                                 NY006610
C      LENGTH * PERCENT STRETCH * 200(D)SCR MEAS. K                         NY006620
C                                                                           NY006630
  546  GO TO (548,550,552,548), J2                                          NY006640
  548  STRL = CLI*(1.0+ELT)                                                NY006650
       GO TO 554                                                            NY006660
  550  STRL = CLI*(1.0+ELT)*D200                                            NY006670
       GO TO 554                                                            NY006680
  552  STRL = CLI*(1.0+ELT)*QN200                                           NY006690
C                                                                           NY006700
C      CALC. HORIZ. EXCUR. (XEX&YEX) AND VERT. HEIGHT(VHT) OF SEG.          NY006710
C                                                                           NY006720
```

```
  554 XEX = (STRL*SIN(CLIN))*COS(ROTN)                                          NY006730
      YEX = (STRL*SIN(CLIN))*SIN(ROTN)                                          NY006740
      VHT = STRL*COS(CLIN)                                                      NY00675C
C                                                                               NY006760
CC    OUTPUT SEGMENT STATISTICS                                                 NY006770
C                                                                               NY006780
      Z = CLIN/RD                                                               NY006790
  557 IF (DONE-1.0) 560,558,558                                                 NY006800
  558 X = ROT/RD                                                                NY006810
      Y = ROTN/RD                                                               NY006820
      VN = VN/CPK                                                               NY006830
      WRITE (LO,32) I,I1,CLI,Z,XEX,YEX,VN,X,Y,UDRGN,VDRGN,DRGT                  NY006840
   32 FORMAT (I3,3X,I2,3X,F5.1,1X,F4.1,2(1X,F5.1),1X,                           NY006850
     13(1X,F5.1),2(1X,F5.2),1X,F8.5)                                            NY006860
C                                                                               NY006870
CC    SUM SEGMENT STATS. WITH COMPONENT TOTAL                                   NY006880
C                                                                               NY006890
  560 DRAG =DRAG+UDRGN                                                          NY006900
      TVHT = TVHT+VHT                                                           NY006910
      TXEX = TXEX+XEX                                                           NY006920
      TYEX = TYEX+YEX                                                           NY006930
      TSTR = TSTR+(STRL-CLI)                                                    NY006940
      TLD = TLD+CLI                                                             NY006950
  562 CONTINUE                                                                  NY006960
C                                                                               NY00697C
CC    TRANSFER COMPONENT STATS. INTO T ARRAYS                                   NY006980
C                                                                               NY006990
      T1(I) = DRAG                                                              NY007000
      T2(I) = Z                                                                 NY007010
      T3(I) = TENS                                                              NY007020
      T4(I) = TVHT                                                              NY007030
      T5(I) = TXEX                                                              NY007040
      T6(I) = TYEX                                                              NY007050
      T7(I) = TSTR                                                              NY007060
      TSTR = 0.0                                                                NY007070
  570 CONTINUE                                                                  NY007080
      RETURN                                                                    NY007090
      END                                                                       NY007100
      SUBROUTINE CONST                                                          NY007110
C     SUBROUTINE CONST - FOR USE WITH PROG. NOYFB, REV. 9.1                     NY007120
CC    INPUT STANDARD WHOI BUOY COMPONENT CHARACTERISTICS                        NY007130
CC    AND STRETCH CHARACTERISTICS AND DRAG COEFFICIENTS                         NY007140
C                                                                               NY007150
      COMMON W(42),A(42),RBS(24),AW(5),E(16)                                    NY007160
      COMMON IT(65),XL(65),TW(66),CDN(5),CDT(5)                                 NY007170
      COMMON DCP(20),CP(20),RCP(20),IHDG(36)                                    NY007180
      COMMON T1(65),T2(65),T3(65),T4(65),T5(65),T6(65),T7(65)                   NY007190
      COMMON IDA(10),IDM(10),MDB(10)                                            NY007200
```

```
      COMMON DPT,GN200,D200,FPM,L11,LO,LO3,NEW,TERMW,TERML                NY007210
      COMMON RD,PI,TL,IC,IV,FUDG,RC,SEG,DONE                             NY007220
      COMMON TCLIN,TTENS,TROTN,QBKUP,TVELO,ANCR,ANCRA                    NY007230
C                                                                        NY007240
C                                                                        NY007250
      TERMW = -2.19                                                      NY007260
      TERML = 0.203                                                      NY007270
      RD = 0.017453293                                                   NY007280
      PI = 3.141592654                                                   NY007290
      FPM = 3.28084                                                      NY007300
C                                                                        NY007310
C     A(I) - AREA OF COMP. IN SQR.METER PER METER LENGTH                 NY007320
C            (LINE,WIRE,CHAIN = DIAMETER IN METERS)                      NY007330
C     W(I) - WEIGHT OF COMP. IN POUNDS PER METER LENGTH                  NY007340
C            (+= POSITIVE BUOYANCY, -= NEGATIVE BUOYANCY)                NY007350
C     RBS(I) - RATED BREAKING STRENGTH IN POUNDS                         NY007360
C     AW(I) - CROSS SECTIONAL METAL AREA OF WIRE IN SQR.INCHES           NY007370
C                                                                        NY007380
C                                                                        NY007390
C     WIRE CONSTANTS: (1)-3/16",(2)-1/4",(3)-5/16",(4)-3/8",(5)-?        NY007400
C     U.S.S.,TORQUE BALANCED JACKETED 3X19 WIRE                          NY007410
C                                                                        NY007420
      A(1) = 6.5786E-03                                                  NY007430
      W(1) = -0.154                                                      NY007440
      RBS(1) = 4000.0                                                    NY007450
      AW(1) = 0.01611                                                    NY007460
      A(2) = 8.3566E-03                                                  NY007470
      W(2) = -0.266                                                      NY007480
      RBS(2) = 6750.0                                                    NY007490
      AW(2) = 0.02738                                                    NY007500
      A(3) = 9.9568E-03                                                  NY007510
      W(3) = -0.41                                                       NY007520
      RBS(3) = 10300.0                                                   NY007530
      AW(3) = 0.04206                                                    NY007540
      A(4) = 1.15824E-02                                                 NY007550
      W(4) = -0.594                                                      NY007560
      RBS(4) = 14800.0                                                   NY007570
      AW(4) = 0.06015                                                    NY007580
      A(5) = 0.0                                                         NY007590
      W(5) = 0.0                                                         NY007600
      RBS(5) = 1.0                                                       NY007610
      AW(5) = 1.0                                                        NY007620
C                                                                        NY007630
C     SAMPSON, SINGLE BRAID DACRON, WHOI SPECS                           NY007640
C     DACRON LINE CONSTANTS: (6)-3/8",(7)-7/16",(8)-1/2",                NY007650
C     (9)-9/16",(10)-5/8"                                                NY007660
C     DIAMETER IS 93.5% OF NOMINAL SIZE                                  NY007670
C                                                                        NY007680
```

```
      A(6) = 8.90588E-03                                                NY007690
      W(6) = -0.0375                                                    NY007700
      RBS(6) = 5700.0                                                   NY007710
      A(7) = 1.03902E-02                                                NY007720
      W(7) = -0.0516                                                    NY007730
      RBS(7) = 7000.0                                                   NY007740
      A(8) = 1.18745E-02                                                NY007750
      W(8) = -0.0667                                                    NY007760
      RBS(8) = 9000.0                                                   NY007770
      A(9) = 1.33588E-02                                                NY007780
      W(9) = -0.0851                                                    NY007790
      RBS(9) = 11200.0                                                  NY007800
      A(10) = 1.48431E-02                                               NY007810
      W(10) = -0.1082                                                   NY007820
      RBS(10) = 14000.0                                                 NY007830
C                                                                       NY007840
CCC   COLUMBIA, SINGLE BRAID PLAITED NYLON, WHOI SPECS                  NY007850
CCCC  NYLON LINE CONSTANTS: (11)-3/8',(12)-1/2',(13)-9/16'              NY007860
CCCC  (14)-5/8',(15)-3/4'                                               NY007870
CCCC  DIAMETER IS 93.5% OF NOMINAL SIZE                                 NY007880
C                                                                       NY007890
      A(11) = 8.90588E-03                                               NY007900
      W(11) = -0.011                                                    NY007910
      RBS(11) = 3700.0                                                  NY007920
      A(12) = 1.18745E-02                                               NY007930
      W(12) = -0.0204                                                   NY007940
      RBS(12) = 6400.0                                                  NY007950
      A(13) = 1.33588E-02                                               NY007960
      W(13) = -0.0261                                                   NY007970
      RBS(13) = 8200.0                                                  NY007980
      A(14) = 1.48431E-02                                               NY007990
      W(14) = -0.033                                                    NY008000
      RBS(14) = 10400.0                                                 NY008010
      A(15) = 1.78118E-02                                               NY008020
      W(15) = -0.0457                                                   NY008030
      RBS(15) = 14200.0                                                 NY008040
C                                                                       NY008050
CCC   UNSPECIFIED SYNTHETIC LINE : (16)-? THROUGH (20)-?                NY008060
C                                                                       NY008070
      A(16) = 0.0                                                       NY008080
      W(16) = 0.0                                                       NY008090
      RBS(16) = 1.0                                                     NY008100
      A(17) = 0.0                                                       NY008110
      W(17) = 0.0                                                       NY008120
      RBS(17) = 1.0                                                     NY008130
      A(18) = 0.0                                                       NY008140
      W(18) = 0.0                                                       NY008150
      RBS(18) = 1.0                                                     NY008160
```

```
      A(19) = 0.0                                                        NY008170
      W(19) = 0.0                                                        NY008180
      RBS(19) = 1.0                                                      NY008190
      A(20) = 0.0                                                        NY008200
      W(20) = 0.0                                                        NY008210
      RBS(20) = 1.0                                                      NY008220
C                                                                        NY008230
C     CHAIN: (21)-1/4',(22)-3/8',(23)-1/2',(24)-3/4'                     NY008240
C                                                                        NY008250
      A(21) = 2.74E-02                                                   NY008260
      W(21) = -2.33                                                      NY008270
      RBS(21) = 5400.0                                                   NY008280
      A(22) = 3.7E-02                                                    NY008290
      W(22) = -5.12                                                      NY008300
      RBS(22) = 12150.0                                                  NY008310
      A(23) = 4.8E-02                                                    NY008320
      W(23) = -9.02                                                      NY008330
      RBS(23) = 21600.0                                                  NY008340
      A(24) = 6.85E-02                                                   NY008350
      W(24) = -19.52                                                     NY008360
      RBS(24) = 48.6E+03                                                 NY008370
C                                                                        NY008380
C     CYLINDRICAL INSTRUMENTS:                                           NY008390
C     DIVISOR IS THE LENGTH OF THE INSTRUMENT (METERS)                   NY008400
C     (25)-VACM,(26)-850(LT),(27)-850(HEAVY),                            NY008410
C     (28)-ENG.CM,,(29)-INCLINOMETER,(30)-DEPTH REC.,                    NY008420
C     (31)-TENSION REC.,(32)-TENSAC                                      NY008430
C     (33)-?,(34)-?,(35)-RELEASE,AMF TRANSPONDING                        NY008440
C                                                                        NY008450
      A(25) = 0.1579                                                     NY008460
      W(25) = -75.0/1.9                                                  NY008470
      A(26) = 0.17917                                                    NY008480
      W(26) = -40.0/1.8                                                  NY008490
      A(27) = 0.17917                                                    NY008500
      W(27) = -50.0/1.8                                                  NY008510
      A(28) = 0.16043                                                    NY008520
      W(28) = -40.0/0.8                                                  NY008530
      A(29) = 0.16043                                                    NY008540
      W(29) = -40.0/0.8                                                  NY008550
      A(30) = 0.16043                                                    NY008560
      W(30) = -40.0/0.8                                                  NY008570
      A(31) = 0.16043                                                    NY008580
      W(31) = -40.0/0.8                                                  NY008590
      A(32) = 0.16875                                                    NY008600
      W(32) = -70.0/1.6                                                  NY008610
      A(33) = 0.0                                                        NY008620
      W(33) = 0.0                                                        NY008630
      A(34) = 0.0                                                        NY008640
```

```
      W(34) = 0.0                                                          NY008650
      A(35) = 0.1499                                                       NY008660
      W(35) = -80.0/1.8                                                    NY008670
C                                                                          NY008680
CCC   SPHERICAL INSTRUMENTS:                                               NY008690
CCC   DIVISOR IS THE LENGTH OF THE INSTRUMENT (METERS)                     NY008700
CCC   (36)-?, (37)-MIT P/T, (38)-RADIC FLOAT                               NY008710
C                                                                          NY008720
      A(36) = 0.0                                                          NY008730
      W(36) = 0.0                                                          NY008740
      A(37) = 0.207                                                        NY008750
      W(37) = -18.0/0.4                                                    NY008760
      A(38) = 0.26                                                         NY008770
      W(38) = 41.0/1.0                                                     NY008780
C                                                                          NY008790
CCC   SPHERES MOUNTED ON 3/8' CHAIN, 1 METER COMPONENT LENGTH              NY008800
CCC   (39)-16' SPHERE - 17.5' O.D., (40)-17' SPHERE-18.5' O.D.             NY008810
CCC                                                                        NY008820
C                                                                          NY008830
      A(39) = 0.25138                                                      NY008840
      W(39) = 43.5                                                         NY008850
      A(40) = 0.26962                                                      NY008860
      W(40) = 53.0                                                         NY008870
C                                                                          NY008880
CCC   UNDEFINED COMPONENTS W/UNIQUE DRAG COEFF.                            NY008890
CCC   (41)-?, (42)-?                                                       NY008900
C                                                                          NY008910
      A(41) = 0.0                                                          NY008920
      W(41) = 0.0                                                          NY008930
      A(42) = 0.0                                                          NY008940
      W(42) = 0.0                                                          NY008950
C                                                                          NY008960
CCC   DRAG COEFFICIENTS - CDN-NORMAL, CDT - TANGENTIAL                     NY008970
CCC   (1)-WIRE,(2)-LINE & CHAIN,(3)-INSTRUMENTS,                           NY008980
CCC   (4)-SPHERES, (5)-UNSPECIFIED                                         NY008990
C                                                                          NY009000
      CDN(1) = 1.3                                                         NY009010
      CDT(1) = 0.007                                                       NY009020
      CDN(2) = 1.3                                                         NY009030
      CDT(2) = 0.007                                                       NY009040
      CDN(3) = 1.2                                                         NY009050
      CDT(3) = 0.9                                                         NY009060
      CDN(4) = 0.5                                                         NY009070
      CDT(4) = 0.5/PI                                                      NY009080
      CDN(5) = 0.0                                                         NY009090
      CDT(5) = 0.0                                                         NY009100
C                                                                          NY009110
C     STRETCH CHARACTERISTICS                                              NY009120
```

```
C      (1-4)-WIRE,(5-8)-DACRON,(9-12)-NYLON,(13-16)-UNSPECIFIED                NY009130
C                                                                              NY009140
       E(1) = 1.428571E-03                                                     NY009150
       E(2) = 20.5E+06                                                         NY009160
       E(3) = 0.0                                                              NY009170
       E(4) = 0.0                                                              NY009180
       E(5) = 2.81E+06                                                         NY009190
       E(6) = 0.607                                                            NY009200
       E(7) = 3.83E+06                                                         NY009210
       E(8) = 0.74                                                             NY009220
       E(9) = 1.56E+05                                                         NY009230
       E(10) = 0.516                                                           NY009240
       E(11) = 1.3262E+05                                                      NY009250
       E(12) = 0.535                                                           NY009260
       E(13) = 0.0                                                             NY009270
       E(14) = 0.0                                                             NY009280
       E(15) = 0.0                                                             NY009290
       E(16) = 0.0                                                             NY009300
       CONTINUE                                                                NY009310
       RETURN                                                                  NY009320
       END                                                                     NY009330
       SUBROUTINE TRANS                                                        NY009340
C                                                                              NY009350
CCC    SUBROUTINE TRANS - FOR USE WITH PROG. NOYFB, REV. 9.1                   NY009360
CCC    CALCULATE AND STORE IN ARRAY (TW), PEAK TENSION ON EACH                 NY009370
CCC    COMPONENT EXPERIENCED DURING ANCHOR LAST LAUNCH                         NY009380
CCC    INITIATES EACH RUN BY DETERMINING TOTAL RELAXED LENGTH (TL)             NY009390
CCC    AND RESERVE BUOYANCY AT COMPONENT NO.1 (QBKUP)                          NY009400
CCC    CALC. TERMINAL VELOCITY OF FREE FALL ANCHOR (TVELO)                     NY009410
C                                                                              NY009420
       COMMON W(42),A(42),RBS(24),AW(5),E(16)                                  NY009430
       COMMON IT(65),XL(65),TW(66),CDN(5),CDT(5)                               NY009440
       COMMON DCP(20),CP(20),RCP(20),IHDG(36)                                  NY009450
       COMMON T1(65),T2(65),T3(65),T4(65),T5(65),T6(65),T7(65)                 NY009460
       COMMON IDA(10),IDM(10),DB(10)                                           NY009470
       COMMON DPT,QN200,D200,FPM,LI1,LO,LO3,NEW,TERMW,TERML                    NY009480
       COMMON RD,PI,TL,IC,IV,FUDG,RC,SEG,DONE                                  NY009490
       COMMON TCLIN,TTENS,TROTN,QBKUP,TVELO,ANCR,ANCRA                         NY009500
       X = 0.0                                                                 NY009510
       J = 0                                                                   NY009520
       DO 420 I = 1, IC                                                        NY009530
  401  I1 = IT(I)                                                              NY009540
C                                                                              NY009550
CC     SUM INPUT LENGTHS (TL) AND COMP. BUOYANCIES (T1(I))                     NY009560
C      T1(I) IS USED FOR TEMPORARY STORAGE                                     NY009570
C                                                                              NY009580
       TL = TL + XL(I) + TERML                                                 NY009590
       X = X+TERMW+W(I1)*XL(I)                                                 NY009600
```

```
      T1(I) = X                                                          NY009610
C                                                                        NY009620
CC    RESERVE BUOYANCY (QBKUP) AT TOP COMP. = SUM OF WEIGHTS             NY009630
CC    OF RELEASE (35) AND ALL COMPONENTS ABOVE IT                        NY009640
C                                                                        NY009650
      IF(J-1) 402,405,405                                                NY009660
  402 QBKUP = X                                                          NY009670
      IF(I1-35) 405,403,405                                              NY009680
  403 J = 2                                                              NY009690
C                                                                        NY009700
CC    DETERMINE DRAG COEFF. SUBSCRIPT (J1), FUNCT. JCD                   NY009710
C                                                                        NY009720
  405 J1 = JCD(I1)                                                       NY009730
C                                                                        NY009740
CC    CALC. TOTAL AREA*CD FOR EACH COMPONENT AND SUM                     NY009750
CC    GO TO 410 - WIRE, LINE AND CHAIN                                   NY009760
C           412 - INSTRUMENTS(CYLINDERS)                                 NY009770
CC          410 - SPHERES                                                NY009780
CC          412 - UNSPECIFIED                                            NY009790
CC    Y = CDT*SURFACE AREA                                               NY009800
C                                                                        NY009810
      Y = CDT(J1)*PI*A(I1)*XL(I)*FPM**2                                  NY009820
      GO TO  (410,410,412,410,412), J1                                   NY009830
410   TW(I+1) = TW(I)+Y                                                  NY009840
      GO TO 420                                                          NY009850
412   TW(I+1) = TW(I)+(CDN(J1)*(PI/4.0)*A(I1)**2                         NY009860
     1*FPM**2)+Y                                                         NY009870
  420 CONTINUE                                                           NY009880
C                                                                        NY009890
CC    CALC. VELO.**2(VSQ), CD*AREA OF ANCHOR APPLIED                     NY009900
CC    THEN CALC. TERMINAL VELOCITY AND TRANSIENT PEAK LOAD               NY009910
C                                                                        NY009920
      VSQ = (ANCR-T1(IC))/(TW(IC+1)+ANCRA*FPM**2*1.15)                   NY009930
      DO 425 I = 1,IC                                                    NY009940
  416 TW(I) = T1(I)+TW(I+1)*VSQ                                          NY009950
  425 CONTINUE                                                           NY009960
      TVELO = (SQRT(VSQ)/FPM)*60.0                                       NY009970
      RETURN                                                             NY009980
      END                                                                NY009990
      SUBROUTINE PTIO                                                    NY010000
C                                                                        NY010010
CC    SUBROUTINE PTIO - FOR USE WITH PROG. NOYFB, REV. 9.1               NY010020
CC    INPUT/OUTPUT SUBROUTINE FOR PERMANENT RECORD OF MOORING            NY010030
CC    SPECIFICALLY FOR USE WITH A PAPER TAPE READER AND PAPER TAPE       NY010040
CC    PUNCH BUT USEABLE WITH OTHER I/O DEVICES                           NY010050
CC    READS/WRITES NUMBER,TYPE AND LENGTH OF MOORING COMPONENTS          NY010060
CC    READS/WRITES CONSTANTS AND VARIABLES USED FOR MOORING CONFIG       NY010070
C     READS/WRITES OPERATOR COMMENTS                                     NY010080
```

```
C                                                                       NY010090
      COMMON W(42),A(42),RBS(24),AW(5),E(16)                            NY010100
      COMMON IT(65),XL(65),TW(66),CDN(5),CDT(5)                         NY010110
      COMMON DCP(20),CP(20),RCP(20),IHDG(36)                            NY010120
      COMMON T1(65),T2(65),T3(65),T4(65),T5(65),T6(65),T7(65)           NY010130
      COMMON IDA(10),IDM(10),DB(10)                                     NY010140
      COMMON DPT,QN200,D200,FPM,LI1,LC,LC3,NEW,TERMW,TERML              NY010150
      COMMON RD,PI,TL,IC,IV,FUDG,RC,SEG,DONE                            NY010160
      COMMON TCLIN,TTENS,TROTN,QBKUP,TVELO,ANCR,ANCRA                   NY010170
   36 FORMAT (4F13.7)                                                   NY010180
   37 FORMAT (I2,F13.7)                                                 NY010190
   38 FORMAT (36(A2))                                                   NY010200
   39 FORMAT (7F8.3,I2)                                                 NY010210
      IF (NEW-15) 1010,1006,1000                                        NY010220
 1000 WRITE (LO3,39) DPT,QN200,D200,ANCR,ANCRA,TERMW,TERML,IC           NY010230
      WRITE (LO3,36) (W(I),A(I),I = 1,42),(RBS(I),I = 1,24),            NY010240
     1(AW(I),I = 1,5),(E(I),I = 1,16),(CDN(I),CDT(I),I = 1,5)           NY010250
      DO 1002 I = 1,IC                                                  NY010260
      WRITE (LO3,37) IT(I),XL(I)                                        NY010270
 1002 CONTINUE                                                          NY010280
      WRITE (LO3,38) (IHDG(I),I = 1,36)                                 NY010290
      GO TO 1010                                                        NY010300
 1006 READ (LI1,39) DPT,QN200,D200,ANCR,ANCRA,TERMW,TERML,IC            NY010310
      READ (LI1,36) (W(I),A(I),I = 1,42),(RBS(I),I = 1,24),             NY010320
     1(AW(I),I = 1,5),(E(I),I = 1,16),(CDN(I),CDT(I),I = 1,5)           NY010330
      DO 1008 I = 1,IC                                                  NY010340
      READ (LI1,37) IT(I),XL(I)                                         NY010350
 1008 CONTINUE                                                          NY010360
      READ (LI1,38) (IHDG(I),I = 1,36)                                  NY010370
 1010 CONTINUE                                                          NY010380
      RETURN                                                            NY010390
      END                                                               NY010400
      FUNCTION JCD(I1)                                                  NY010410
C                                                                       NY010420
C     FUNCTION JCD - USE WITH PROG. NOYFB, REV 9.1                      NY010430
C     SET SUBSCRIPT FOR COMPONENT DRAG COEFFICIENTS (J1)                NY010440
C     (5) -        '     41 AND 42                                      NY010450
C     (4) -        '     36 THRU 40                                     NY010460
C     (3) -        '     25   '  35                                     NY010470
C     (2) -        '      6   '  24                                     NY010480
C     (1) -        '      1   '   5                                     NY010490
C                                                                       NY010500
      JCD = 5                                                           NY010510
      IF (I1-41) 483,487,487                                            NY010520
  483 JCD = 4                                                           NY010530
      IF (I1-36) 484,487,487                                            NY010540
  484 JCD = 3                                                           NY010550
      IF (I1-25) 485,487,487                                            NY010560
```

```
485 JCD = 2                                                    NY010570
    IF (I1-6) 486,487,487                                      NY010580
486 JCD = 1                                                    NY010590
487 CONTINUE                                                   NY010600
    RETURN                                                     NY010610
    END                                                        NY010620
```



Figure 43. Temperature (°C) on a vertical section for the Cape San Martin line on 27-28 November 1978.



Figure 44. Temperature (°C) on a vertical section for the Slate Rock line on 27-28 November 1978.



Figure 45. Temperature (°C) on a vertical section for the Cape San Martin line on 8-9 January 1979.



Figure 46. Temperature (°C) on a vertical section for the Slate Rock line on 8-9 January 1979.



Figure 47. Temperature (°C) on a vertical section for the Cape San Martin line on 22-23 January 1979.



Figure 48. Temperature (°C) on a vertical section for the Slate Rock line on 22-23 January 1979.



Figure 49. Temperature (°C) on a vertical section for the Cape San Martin line on 21-22 February 1979.



Figure 50. Temperature (°C) on a vertical section for the Slate Rock line on 21-22 February 1979.



Figure 51. Sigma-t on a vertical section for the Cape San Martin line on 27-28 November 1978.



Figure 52, Sigma-t on a vertical section for the Slate Rock line on 27-28 November 1979.



Figure 53. Sigma-t on a vertical section for the Cape San Martin line on 8-9 January 1979.



Figure 54. Sigma-t on a vertical section for the Slate Rock line on 8-9 January 1979.



Figure 55. Sigma-t on a vertical section for the Cape San Martin line on 22-23 January 1979.



Figure 56. Sigma-t on a vertical section for the Slate Rock line on 22-23 January 1979.



Figure 57. Sigma-t on a vertical section for the Cape San Martin line on 21-22 February 1979.



Figure 58. Sigma-t on a vertical section for the Slate Rock line on 21-22 February 1979.



Figure 59. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 27-28 November 1978.



Figure 60. Sound speed (m/sec) on a vertical section for the Slate Rock line on 27-28 November 1978.



Figure 61. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 8-9 January 1979.



Figure 62. Sound speed (m/sec) on a vertical section for the Slate Rock line on 8-9 January 1979.



Figure 63. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 22-23 January 1979.



Figure 64. Sound speed (m/sec) on a vertical section for the Slate Rock line on 22-23 January 1979.



Figure 65. Sound speed (m/sec) on a vertical section for the Cape San Martin line on 21-22 February 1979.



Figure 66. Sound speed (m/sec) on a vertical section for the Slate Rock line on 21-22 February 1979.



Figure 67. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Cape San Martin line on 27-28 November 1978.



Figure 68. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Slate Rock line on 27-28 November 1978.



Figure 69. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Cape San Martin line on 8-9 January 1979.



Figure 70. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Slate Rock line on 8-9 January 1979.



Figure 71. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Cape San Martin line on 22-23 January 1979.



Figure 72. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Slate Rock line on 22-23 January 1979.



Figure 73. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Cape San Martin line on 21-22 February 1979.



Figure 74. Sigma-t, solid line, and Salinity (‰), dashed line, superimposed on a vertical section for the Slate Rock line on 21-22 February 1979.

BIBLIOGRAPHY

1. Bernstein, R.L., Breaker L., and Whritner, R., "California Current Eddy Formation: Ship, Air, and Satellite Results," Science, v. 195, p. 353-359, 28 January 1977.

2. Greer, R.E., Mesoscale Components of the Geostrophic Flow and its Temporal and Spatial Variability in the California Current off Monterey Bay in 1973-74, Masters Thesis, Naval Postgraduate School, Monterey, California, 1975.

3. Halpern, D., Smith, R.L., and Reed, R.K., "On the California Undercurrent Over the Continental Slope Off Oregon," Journal of Geophysical Research, v. 83, p. 1366-1372, 20 March 1978.

4. Hickey, B.M., "The California Current System - Hypothesis and Facts," Contribution Number 1038 of the Department of Oceanography, University of Washington, 24 April 1978.

5. Hughes, J.G., The Spatial and Temporal Variation of Sound Speed in the California Current System Off Monterey, California, Masters Thesis, Naval Postgraduate School, Monterey, California, 1975.

6. Huyer, A., "Seasonal Variation in Temperature, Salinity, and Density Over the Continental Shelf Off Oregon," Limnology and Oceanography, v. 22(3), p. 442-445, May 1977.

7. Huyer, A., Hickey, B.M., Smith, J.D., Smith, R.L., and Pillsbury, R.D., "Alongshore Coherence at Low Frequencies in Currents Observed Over the Continental Shelf Off Oregon and Washington," Journal of Geophysical Research, v. 80(24), p. 3495-3505, 20 August 1975.

8. Huyer, A. and Smith, R.L., "Physical Characteristics of Pacific Northwest Coastal Waters," The Marine Plant Biomass of the Pacific Northwest Coast, p. 37-47, 1978.

9. McCreary, J.P., Eastern Ocean Response to Changing Wind Systems, Ph.D Dissertation, University of California, San Diego, 1977.

10. Molnar, D.L., California Undercurrent Reconnaissance Between Monterey and Santa Barbara, Masters Thesis, Naval Postgraduate School, Monterey, California, 1972.

11. Mooers, C.N.K., Collins, C.A., and Smith, R.L., "The Dynamic Structure of the Frontal Zone in the Coastal Upwelling Region Off Oregon," Journal of Physical Oceanography, v. 6, p. 3-21, January 1976.

12. Mysak, L.A., "On the Stability of the California Undercurrent Off Vancouver Island," Journal of Physical Oceanography, v. 7, p. 904-917, November 1977.

13. NOAA Technical Report NMFS SSRF-718, Surface Currents as Determined by Drift Card Releases Over the Continental Shelf Off Central and Southern California, by J.L. Squire, Jr., p. 11, December 1977.

14. Pavlova, Yu. V., "Seasonal Variations of the California Current," Oceanology, v. 13, p. 806-814, August 1967.

15. Reid, J.L., Jr., "Measurements of the California Countercurrent at a Depth of 250 Meters," Journal of Marine Research, v. 20, p. 134-137, 15 July 1962.

16. Reid, J.L., Jr., "Measurements of the California Countercurrent Off Baja California," Journal of Geophysical Research, v. 68, p. 4819-4822, 15 August 1963.

17. Reid, J.L., Jr., Roden, G.I., and Wyllie, J.G., "Studies of the California Current System," California Cooperative Oceanic Fisheries Investigation Progress Report, p. 27-56, 1958.

18. Reid, J.L., Jr., and Schwatzlose, R.A., "Direct Measurements of the Davidson Current Off Central California," Journal of Geophysical Research, v. 67, p. 559-565, June 1962.

19. Smith, R.L., Pattullo, J.G., and Lane, R.K., "An Investigation of the Early Stage of Upwelling Along the Oregon Coast," Journal of Geophysical Research, v. 71(4), p. 1135-1140, 15 February 1966.

20. Sverdrup, H.U. and Fleming, R.H., "The Waters Off the Coast of Southern California," Scripps Institute of Oceanography Bulletin, v. 4, p. 261-375, 9 October 1941.

21. Sverdrup, H.U., Johnson, M.W., and Fleming, R.H., The Oceans: Their Physics, Chemistry, and General Biology, 23rd ed., Prentice-Hall, Inc., 1942.

22. Wickham, J.B., "Observations of the California Undercurrent," Journal of Marine Research, v. 33, p. 325-340, September 1975.

23. Wilson, W.D., "Speed of Sound in Sea Water as a Function of Temperature, Pressure, and Salinity," Journal of Acoustical Society of America, v. 32, p. 1357, 1960.

24. Woods Hole Oceanographic Institution Technical Report WHOI-73-71, Details of Woods Hole Moorings, by R.H. Heinmiller, and R.G. Walden, October 1973.

25. Woods Hole Oceanographic Institution Report WHOI-76-59, A Computer Program for the Design of a Single-Point Subsurface Mooring Systems: NOYFB, by D.A. Moller, June 1976.

26. Wooster, W.S. and Jones, J.H., "California Undercurrent Off Northern Baja California," Journal of Marine Research, v. 28, p. 235-250, 15 May 1970.

27. Wyllie, J.G., "Geostrophic Flow of the California Current at the Surface and at 200 Meters," California Cooperative Oceanic Fisheries Investigation, Atlas No. 4, December, 1966.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Chairman Code 68 Department of Oceanography Naval Postgraduate School Monterey, CA 93940	3
2.	Director Naval Oceanography Division (OP952) Navy Department Washington, DC 20350	1
3.	Office of Naval Research Code 480 Naval Ocean Research and Development Activity NSTL Station, MS 39529	1
4.	Dr. Robert E. Stevenson Scientific Liaison Office, ONR Scripps Institution of Oceanography La Jolla, CA 92037	1
5.	SIO Library University of California, San Diego P.O. Box 2367 La Jolla, CA 92037	1
6.	Department of Oceanography Library University of Washington Seattle, WA 98105	1
7.	Department of Oceanography Library Oregon State University Corvallis, OR 97331	1
8.	Commanding Officer Fleet Numerical Weather Central Monterey, CA 93940	1
9.	Commanding Officer Naval Environmental Prediction Research Facility Monterey, CA 93940	1
10.	Commander Oceanographic Systems Pacific Box 1390 Pearl Harbor, Hawaii 96860	1

11. Defense Documentation Center — 2
Cameron Station
Alexandria, VA 22314

12. Library Code 0142 — 2
Naval Postgraduate School
Monterey, CA 93940

13. Commanding Officer — 1
Naval Ocean Research and Development Activity
NSTL Station, MS 39529

14. Commander — 1
Naval Oceanography Command
NSTL Station, MS 39529

15. Commanding Officer — 1
Naval Oceanographic Office
NSTL Station, MS 39529

16. Dr. S.P. Tucker Code 68Tx — 4
Department of Oceanography
Naval Postgraduate School
Monterey, CA 93940

17. Professor J.B. Wickham Code 68Wk — 4
Department of Oceanography
Naval Postgraduate School
Monterey, CA 93940

18. Commandant (G-PTE-1/72) — 2
U.S. Coast Guard
400 7th Street S.W.
Washington, DC 20590

19. Lt. K. Coddington — 5
Department of Ocean Sciences
U.S. Coast Guard Academy
New London, CT 06320

28657

Thesis 185670
C53025 Coddington
c.1 Measurement of the California counter-current.

28657

Thesis 185670
C53025 Coddington
c.1 Measurment of the California counter-current.

thesC53025
Measurement of the California counter-cu
3 2768 002 09452 6
DUDLEY KNOX LIBRARY